



Decorative Stainless Steel Sheet

Metal Cabinet

Commercial Entrance Door

Metal Ceiling

Stainless Steel Trim/Profile

Metal Cladding

Metal Signage

Water Ripple Stainless Steel Board

Stainless Steel Profile

Precision Finishing System

Product Brochure



Contents

产品目录

转角收口系列
Corner Finishing Series

01

P01-P12

平面过渡系列
Flat Transition Series

02

P13-P23

地板收口系列
Floor Finishing Series

03

P24-P36

踏步台面系
Step Platform System

04

P37-P42

踢脚线系
Skirting Board System

05

P43-P66

门套收口系列
Door Frame Finishing Series

06

P67-PT3

墙板收口系列
Wall Panel Finishing Series

07

P74-P82

批灰收口系
Plastering Finishing Series

08

P83-P113

黄铜收口系
Brass Finishing Series

09

P114-P130

不锈钢收口系列
Stainless Steel Finishing Series

10

P131-P136

施工工艺规范要求
Construction Process Specification

11

P139-P144



转角收口系列 Corner Profile Series

覆盖墙角、阳角、窗台、玻璃墙边等墙面与地板衔接角等。安装简便，施工快捷，持久耐用，方便护理，效果美观。

Covering External And Internal Corners, Base Frames, And Feature Wall Edging. Utilizing Corner Joints For Functional Applications Simplifies Traditional Processes, Facilitates Straightforward Installation, Ensures Durable Quality, Allows For Easy Maintenance, And Delivers An Aesthetically Pleasing Finish.

www.lmcmetal.com



Corner

CHS- 铝合金阳角防护条 | CHS - Aluminum Alloy External Corner Protection Strip

型 号 Model:	CHS01
面宽尺寸 Front Width:	3mm
长 度 Length:	3 米/米
材 质 Material:	铝合金 Aluminum Alloy
表面颜色 Surface Colour:	多种工艺 多种可选 Multiple Finishes Available
安装结构 Corner Fittings:	安装方便，简化工序 Easy Installation, Simplified Process



阳角防护条
Corner Guard Strip

表面材料
Surface Material

可粘贴
Adhesive Layer

基层墙体
Base Wall



产品应用：阳角收口

Product Application: External Corner Trimming




安装说明：按照尺寸切割后安装，确保贴合度，安装便捷，持久耐用。

Installation Procedure: Install After Reserving Dimensions For The Profile, Secure With Glue/Gasket. Installation Is Straightforward And Grounded.



型 号 (Model)	CH201
进口高度 (Closure Height)	8mm 以上 (8mm 以上) (海唇口)
长 度 (Length)	1.0 米 (m)
材 质 (Material)	铝合金 (Aluminum Alloy)
表面颜色 (Surface Colour)	多种可选 (颜色可选) (Multiple Finishes Available)
安装方式 (Carrier Fitment)	“零”安装、零位工作 (Zero Installation, Simplified Process)







资料来源:根据《2010年中国统计年鉴》、《2010年中国人口统计年鉴》、《2010年中国农村统计年鉴》、《2010年中国城市统计年鉴》、《2010年中国工业统计年鉴》整理。

Installation/Procedure: Install After Reserving Dimensions For The Profile, Insert With Climate Sealant. Installation Is Reinforced And Unreinforced.



型 号 (Model)	LYM1, LYM2, LYM3
柜 体 厚 度 (Cabinet Weight)	8mm, 10mm, 12mm
柜 体 长 度 (Length)	2175/2310 (mm)
柜 体 材 质 (Material)	铝 合 金 (Aluminium Alloy)
柜 体 颜 色 (Cabinet Colour)	粉 红 色 (Pink) / 多 色 选 择 (Multiple Patches Available)
安 装 方 式 (Installation Method)	吊 装 (Hanging)



姓名: _____ 学号: _____ 班级: _____ 日期: _____

Installation Procedures Profiles: Must be installed Concurrently With Primary Materials, Covered Using The following: Installers use its Reinforcement and Strengthened.




LFC - 阳角弧形收口线 | LFC - Curved Corner Trim

型 号 Model:	LFC15, LFC10, LFC12.5, LFC15
收口高度 Closure Height:	6mm, 10mm, 12.5mm, 15mm
长 度 Length:	2.5 Meters
材 质 Material:	铝合金 Aluminum Alloy
表面处理 Surface Colour:	多种工艺 颜色可选 Multiple Finishes Available
安装说明 Installation Details:	安装方便, 简化工序 Easy Installation, Simplified Procedures



产品应用：阳角收口、阳角包边、可
做单面收口、双面收口、半包边
口

Product Applications: External
Corner Finishing, Internal Corner
Finishing, Single-sided Finishing
For Feature Walls, semi Semi-
tion Finishing, half-wall Finishing.



安装说明：首
先确认墙体结构
牢固，然后
将LFC角线
嵌入墙体，用
螺丝固定，半
包边，半包边
口

Installation
Procedures: Must
be installed
securely
with Primary
Materials.
Secure
Using Tite
Adhesive.
Installation is
Simplified
and
Streamlined.




L7 - 阳角单边L形收口线 | L7 - Single-sided L-shaped Corner Trim For External Corners

型 号 Model:	L718, L715, L712.5, L710, L718
收口高度 Closure Height:	6mm, 10mm, 12.5mm, 15mm, 18mm
长 度 Length:	2.5 Meters
材 质 Material:	铝合金 Aluminum Alloy
表面处理 Surface Colour:	多种工艺 颜色可选 Multiple Finishes Available
安装说明 Installation Details:	见 See



产品应用：阳角收口、阳角包边、可
做单面收口、双面收口、半包边
口

Product Applications: External
Corner Finishing, Internal Corner
Finishing, Single-sided Finishing
For Feature Walls, semi Semi-
tion Finishing, half-wall Finishing.



安装说明：首
先确认墙体结构
牢固，然后
将L7角线
嵌入墙体，用
螺丝固定，半
包边，半包边
口

Installation
Procedures: Must
be installed
securely
with Primary
Materials.
Secure
Using Tite
Adhesive.
Installation is
Simplified
and
Streamlined.



ZYMC - 小圆角边收口线 | ZYMC - Small Radius External Corner Trim

型 号 Model:	ZYMC09
收口高度 Closure Height:	15mm
长 度 Length:	2.7 Meters
材 质 Material:	铝合金 Aluminium Alloy
表面颜色 Surface Colour:	多种工艺 颜色可选 Multiple Finishes Available
安装规格 Corner Fitting:	安装方便, 简化工序 Easy Installation, Simplified Procedures



产品应用 - 边收口, 阳角收口, 窗套收口(边收口), 窗套收口(阳角收口)

Product Applications: External Corner Finishing, Internal Corner Finishing, Single-sided Finishing For Feature Wall, Local Transition Finishing, Half-wall Finishing.



安装说明 - 安装前与墙体基层施工, 安装后, 安装完成, 完工后

Installation Procedure: Profiles Must Be Installed Carefully With Primary Materials, Covered Using The Adhesive. Installation Is Straightforward and Groundwork.



ZY1L - 阳角单边收口线 | ZY1L - Single-sided Corner Trim For External Corners


型 号 Model:	ZY1L, ZY1L2
收口高度 Closure Height:	15mm, 12.5mm
长 度 Length:	2.5 Meters
材 质 Material:	铝合金 Aluminium Alloy
表面颜色 Surface Colour:	多种工艺 颜色可选 Multiple Finishes Available
安装规格 Installation Status:	1



产品应用 - 边收口, 阳角收口, 窗套收口(边收口), 窗套收口(阳角收口), 窗套收口(阳角收口), 窗套收口(阳角收口)



安装说明 - 安装前与墙体基层施工, 安装后, 安装完成, 完工后





LFC - 阳角方形收口线 | LFC - Square-Corner Trim Moulding

型 号 Model:	LFC10, LFC11, LFC15
收口高度 Closure Height:	10mm, 15mm, 15.5mm
长 度 Length:	2.5 M/m
材 质 Material:	铝合金 Aluminium Alloy
表面颜色 Surface Colour:	多种工艺 多种可选 Multiple Finishes Available
安装说明 Installation Status:	安装方便, 简化工序 Easy Installation, Simplified Procedures



图 1 阳角收口线
Internal Corner Fitting for
External and Internal Corners



产品应用: 阳角收口, 阳角收口, 阳角收口, 阳角收口, 阳角收口

Product Applications: External Corner Finishing, Internal Corner Finishing, Single-curtain Finishing, For Partition Walls, Joint Transition Finishing, Half-wall Finishing.



安装说明: 阳角收口线, 阳角收口, 阳角收口, 阳角收口, 阳角收口

Installation Procedure: Profiles must be installed Concurrently with Primary Materials, Connect using the Adhesive. Installation is straightforward and streamlined.



CHT - 阳角角收口线 | CHT - Collapse Corner Trim

型 号 Model:	CHT12
收口高度 Closure Height:	12mm
长 度 Length:	2.5 M/m
材 质 Material:	铝合金 Aluminium Alloy
表面颜色 Surface Colour:	多种工艺 多种可选 Multiple Finishes Available
安装说明 Installation Details:	1



图 1 阳角收口线
Internal Corner Fitting for
External and Internal Corners

图 1 阳角收口线
Internal Corner Fitting for
External and Internal Corners



产品应用: 阳角收口, 阳角收口, 阳角收口, 阳角收口, 阳角收口

Product Applications: External Corner Finishing, Internal Corner Finishing, Single-curtain Finishing, For Partition Walls, Joint Transition Finishing, Half-wall Finishing.



安装说明: 阳角收口线, 阳角收口, 阳角收口, 阳角收口, 阳角收口

Installation Procedure: Profiles must be installed Concurrently with Primary Materials, Connect using the Adhesive. Installation is straightforward and streamlined.



YS- 阳角收口线 | YS- Internal Corner Trim

型 号 Model:	YS1, YS2, YS3
收口高度 Closure Height:	12mm, 16mm, 20mm
长 度 Length:	2.5 Meters
材 质 Material:	铝合金 Aluminium Alloy
表面颜色 Surface Colour:	多种工艺 颜色可选 Multiple Finishes Available
安装说明 Installation Status:	安装方便, 简化工序 Easy Installation, Simplified Procedures



产品应用: 阳角收口, 阴角收口, 踢脚线收口, 半墙收口
Product Applications: External Corner Finishing, Internal Corner Finishing, Joint Transition Finishing, Half wall Finishing



安装说明: 在墙体与天花板的交接处, 使用 YS-1 阳角收口线, 安装简单, 省时省力。
Installation Procedures: Must Be Installed Concurrently With Primary Materials, Secure Using The Adhesive. Installation Is Straightforward And Guaranteed.



全屋精细收口/场景应用

Precision Finishing Throughout The House / Scenario Application

电视背景墙应用

Television Backdrop Wall Application





平面过渡系列 Floor/wall Transitions Series

适用于门框口、窗洞空间、楼梯、电梯、玻璃幕墙等新材料过渡、分缝、连接构造、施工便捷、耐久耐用、方便护理、效果美观

Also Known As: Flat angle Building, Covering Tiles, Wall Panels, Polished,
And Half-round or L Profiled Walls
Transitioning, Joining, And Connecting Functions: Straightforward Installation
Enduring Appeal: Easy Maintenance, Aesthetically Pleasing Results

www.lmcmetal.com




CTAs- 平面过渡丁字条 | CTAs- Flat Transition T-bar

型 号 Model:	CTAs-10
接口高度 Closure Height:	10mm
长 度 Length:	2.5 M/m
材 质 Material:	铝合金 Aluminium Alloy
表面颜色 Surface Colour:	多种工艺 多种可选 Multiple Finishes Available
安装说明 Installation Details:	/



产品应用：电梯、玻璃门框等口

Product Application: Elevator, Glass Door Frame, etc.




安装说明：型材需与主材同时施工，即铺贴型材，安装使用，同
施工法。

Installation: Profiles Must Be Installed Concomitantly With Primary Materials, Secured With Adhesive Sealant Installation Is Straightforward, Simplifying The Process




CTA- 平面的金属条 | CTA - Flat Transition Profile

宽度尺寸 Fretwork Width:	CTA110
收口高度 Closure Height:	8mm
长 度 Length:	2.5 Meters
材 质 Material:	铝合金 Aluminium Alloy
表面颜色 Surface Colour:	多种工艺 多种可选 Multiple Finishes Available
安装详情 Installation Details:	/



产品应用 | 用途 | 使用场合 | 点

Product Application: Floor to wall Transition Zone



安装说明：将金属条插入地板与墙壁的缝隙，安装牢固，固定完毕。

Installation Procedure: Insert Edge Gap For Subsequent Installation Of Profile, Secure With Screw-Drivers. This Profile Needs Straightforward Installation And Groundwork Process.



CTX Flat Metal Closure | CTX Flat Profile Transition Strip


宽度尺寸 Fretwork Width:	CTX100, CTX150, CTX200, CTX250, CTX3, CTX5, CTX10
收口高度 Closure Height:	10mm, 15mm, 20mm, 25mm
长 度 Length:	2.5 Meters
材 质 Material:	铝合金 Aluminium Alloy
表面颜色 Surface Colour:	多种工艺 多种可选 Multiple Finishes Available
安装详情 Installation Details:	/




产品应用 | 用途 | 使用场合 | 点
Product Application: Transition Zone for Floor to wall transitions in Wooden Flooring, Ceramic Tiles, Stone Surfaces, And Other Materials Suitable for Woodings for Ceiling Profiles.




安装说明：将金属条插入地板与墙壁的缝隙，安装牢固，固定完毕。
Installation Procedure: Insert Edge Gap For Subsequent Installation Of Profile, Secure With Screw-Drivers. This Profile Needs Straightforward Installation And Groundwork Process.






CT-T 密封胶条 | CT-T Profile Clip

适用尺寸 Fitting Size:	CT-101, CT-102, CT-103, CT-104, CT-105
胶条高度 Closure Height:	10mm, 10mm, 10mm
长 度 Length:	2.0 Meters
材 质 Material:	铝合金 Aluminum Alloy
表面颜色 Surface Colour:	多种工艺 颜色可选 Multiple Finishes Available
安装说明 Installation Details:	↓



产品应用：幕墙、玻璃幕墙等

Product Application: Curtain Wall, Glass Curtain Wall, etc.




安装说明：将密封胶条插入幕墙缝隙中，安装便捷，施工方便。

Installation Procedure: Insert Sealant into the Gap Between Panels. Straightforward Installation and Inconspicuous Process.



CTH-T 密封胶条 | CTH-T Curved Edge Seal

适用尺寸 Fitting Size:	CTH-T1, CTH-T2
胶条高度 Closure Height:	10mm, 10mm
长 度 Length:	2.0 Meters
材 质 Material:	铝合金 Aluminum Alloy
表面颜色 Surface Colour:	多种工艺 颜色可选 Multiple Finishes Available
安装说明 Installation Details:	↓



产品应用：幕墙、玻璃幕墙等

Product Application: Curtain Wall, Glass Curtain Wall, etc.




安装说明：将密封胶条插入幕墙缝隙中，安装便捷，施工方便。


Installation Procedure: Insert Sealant into the Gap Between Panels. Straightforward Installation and Inconspicuous Process.




型 号 (Model)	CP400, CP400S, CP401
额定尺寸 (Rated Width)	8mm, 16mm, 125mm
长 度 (Length)	3 (m)
材 质 (Material)	铝镁合金 / Aluminum Alloy
表面处理 (Surface Colour)	阳极氧化、粉末喷涂 / Multiple Finishes Available
安装附件 (Installation Details)	J



型 号 / Model:	LPETEC-A, LPETEC-L
遮光高度 / Closure Height:	11mm, 14.5mm
长 度 / Length:	2.8 米/m
材 质 / Material:	铝合金 / Aluminium Alloy
表面颜色 / Surface Colour:	白色, 黑色 / Silver-white, Matt Black
安装说明 / Installation Details:	2



Available in French, German, Italian, Spanish, Portuguese, and Chinese (Mandarin and Cantonese)

[illegible]

Installation Procedure: Profiles must be installed concurrently with primary substrate, secured using the adhesive - Once hardware required sealing with silicone caulk - Installation is straightforward, smoothing the process




LFB- 双层沟槽发光玻璃夹 | LFB- Double-grooved Edge Illuminated Glass Clamp

型 号 Model:	LFB001 (双层沟槽发光夹)
收口高度 Closure Height:	12mm
长 度 Length:	2.0 Meters
材 质 Material:	铝合金 Aluminum Alloy
表面颜色 Surface Colour:	哑黑 Matte Black
安装说明 Installation Details:	/



产品应用：玻璃门框收口、玻璃隔断收口

Product Application: Concealed Glass Screens, Partitions And Other Finishing Details



安装说明：安装前与主材师傅沟通，确认安装位置，玻璃表面做好保护膜，安装时注意，避免划伤。

Installation Precaution: Profiles Must Be Installed Concurrently With Primary Materials, Reserved Using The Invisible Glass Elements Requires Sealing With Silicone Sealant Installation Is Straightforward Simplifying The Process

全屋精细收口/场景应用

Precision Finishing Throughout The House / Scenarios Application

浴室应用

Bathroom Application



全屋精细收口/场景应用

Precision Finishing Throughout the House / Scenario applications

背景墙应用

Feature: Wall Application



地板收口系列

Floor Closing Series

用于瓷砖、地板、木地板等不同材料之间的地板收口
过渡、分隔、连接功能。施工便捷，耐久美观，方便维护，装饰性强


Transition Trims For Floor Transitions Between Different Materials Such As Tiles, Wall Panels, And
Wooden Flooring

Features: Seamless Transitions, Joint Separation, Connection Functionality, Straightforward Installation,
Enduring Quality, Easy Maintenance, And An Aesthetically Pleasing Finish

www.lmcmetal.com



型 号 (Model):	LEP10, LEP12, LEP16, LEP18, LEP20, LEP30
最大高度 (Clearance Height):	10mm, 12mm, 16mm, 18mm, 20mm, 30mm
长 度 (Length):	2.7 米 (9 英尺)
材 质 (Material):	铝合金 (Aluminum Alloy)
表面颜色 (Surface Color):	银 (上表面可用) (Bright Finish Available) 其他颜色可定制 (Custom Colors Available)
安装选项 (Installation Details):	见 F



Product Application:
Floor-to-wall Transition Strip
2-Step and Recessed Transition Strip
With Blade Finer Capable Of
Conceal Hardware




1. **Introduction**
 2. **Background**
 3. **Methodology**
 4. **Results**
 5. **Conclusion**



型 号 (Model)	CVS001, CVS001, CVS002, CVS003, CVS004, CVS005, CVS006, CVS007
绳口长度 (Cable Length)	10-15, 10-15, 10-20, 10-20, 10-20, 20-25, 20-25, 20-25mm
绳 径 (Cable)	3.0 mm
材 质 (Material)	铝包钢 (Aluminum-coated Steel)
使用温度 (Service Celsius)	-40°C ~ 120°C
认证/标准 (Certification/Standard)	ISO 9001, ISO 14001, ISO 45001, ISO 50001, ISO 26000, ISO 27001, ISO 28000, ISO 29001, ISO 30001, ISO 31000, ISO 34000, ISO 35000, ISO 36000, ISO 37000, ISO 38000, ISO 39000, ISO 40000, ISO 41000, ISO 42000, ISO 43000, ISO 44000, ISO 45000, ISO 46000, ISO 47000, ISO 48000, ISO 49000, ISO 50000, ISO 51000, ISO 52000, ISO 53000, ISO 54000, ISO 55000, ISO 56000, ISO 57000, ISO 58000, ISO 59000, ISO 60000, ISO 61000, ISO 62000, ISO 63000, ISO 64000, ISO 65000, ISO 66000, ISO 67000, ISO 68000, ISO 69000, ISO 70000, ISO 71000, ISO 72000, ISO 73000, ISO 74000, ISO 75000, ISO 76000, ISO 77000, ISO 78000, ISO 79000, ISO 80000, ISO 81000, ISO 82000, ISO 83000, ISO 84000, ISO 85000, ISO 86000, ISO 87000, ISO 88000, ISO 89000, ISO 90000, ISO 91000, ISO 92000, ISO 93000, ISO 94000, ISO 95000, ISO 96000, ISO 97000, ISO 98000, ISO 99000, ISO 100000, ISO 101000, ISO 102000, ISO 103000, ISO 104000, ISO 105000, ISO 106000, ISO 107000, ISO 108000, ISO 109000, ISO 110000, ISO 111000, ISO 112000, ISO 113000, ISO 114000, ISO 115000, ISO 116000, ISO 117000, ISO 118000, ISO 119000, ISO 120000, ISO 121000, ISO 122000, ISO 123000, ISO 124000, ISO 125000, ISO 126000, ISO 127000, ISO 128000, ISO 129000, ISO 130000, ISO 131000, ISO 132000, ISO 133000, ISO 134000, ISO 135000, ISO 136000, ISO 137000, ISO 138000, ISO 139000, ISO 140000, ISO 141000, ISO 142000, ISO 143000, ISO 144000, ISO 145000, ISO 146000, ISO 147000, ISO 148000, ISO 149000, ISO 150000, ISO 151000, ISO 152000, ISO 153000, ISO 154000, ISO 155000, ISO 156000, ISO 157000, ISO 158000, ISO 159000, ISO 160000, ISO 161000, ISO 162000, ISO 163000, ISO 164000, ISO 165000, ISO 166000, ISO 167000, ISO 168000, ISO 169000, ISO 170000, ISO 171000, ISO 172000, ISO 173000, ISO 174000, ISO 175000, ISO 176000, ISO 177000, ISO 178000, ISO 179000, ISO 180000, ISO 181000, ISO 182000, ISO 183000, ISO 184000, ISO 185000, ISO 186000, ISO 187000, ISO 188000, ISO 189000, ISO 190000, ISO 191000, ISO 192000, ISO 193000, ISO 194000, ISO 195000, ISO 196000, ISO 197000, ISO 198000, ISO 199000, ISO 200000, ISO 201000, ISO 202000, ISO 203000, ISO 204000, ISO 205000, ISO 206000, ISO 207000, ISO 208000, ISO 209000, ISO 210000, ISO 211000, ISO 212000, ISO 213000, ISO 214000, ISO 215000, ISO 216000, ISO 217000, ISO 218000, ISO 219000, ISO 220000, ISO 221000, ISO 222000, ISO 223000, ISO 224000, ISO 225000, ISO 226000, ISO 227000, ISO 228000, ISO 229000, ISO 230000, ISO 231000, ISO 232000, ISO 233000, ISO 234000, ISO 235000, ISO 236000, ISO 237000, ISO 238000, ISO 239000, ISO 240000, ISO 241000, ISO 242000, ISO 243000, ISO 244000, ISO 245000, ISO 246000, ISO 247000, ISO 248000, ISO 249000, ISO 250000, ISO 251000, ISO 252000, ISO 253000, ISO 254000, ISO 255000, ISO 256000, ISO 257000, ISO 258000, ISO 259000, ISO 260000, ISO 261000, ISO 262000, ISO 263000, ISO 264000, ISO 265000, ISO 266000, ISO 267000, ISO 268000, ISO 269000, ISO 270000, ISO 271000, ISO 272000, ISO 273000, ISO 274000, ISO 275000, ISO 276000, ISO 277000, ISO 278000, ISO 279000, ISO 280000, ISO 281000, ISO 282000, ISO 283000, ISO 284000, ISO 285000, ISO 286000, ISO 287000, ISO 288000, ISO 289000, ISO 290000, ISO 291000, ISO 292000, ISO 293000, ISO 294000, ISO 295000, ISO 296000, ISO 297000, ISO 298000, ISO 299000, ISO 300000, ISO 301000, ISO 302000, ISO 303000, ISO 304000, ISO 305000, ISO 306000, ISO 307000, ISO 308000, ISO 309000, ISO 310000, ISO 311000, ISO 312000, ISO 313000, ISO 314000, ISO 315000, ISO 316000, ISO 317000, ISO 318000, ISO 319000, ISO 320000, ISO 321000, ISO 322000, ISO 323000, ISO 324000, ISO 325000, ISO 326000, ISO 327000, ISO 328000, ISO 329000, ISO 330000, ISO 331000, ISO 332000, ISO 333000, ISO 334000, ISO 335000, ISO 336000, ISO 337000, ISO 338000, ISO 339000, ISO 340000, ISO 341000, ISO 342000, ISO 343000, ISO 344000, ISO 345000, ISO 346000, ISO 347000, ISO 348000, ISO 349000, ISO 350000, ISO 351000, ISO 352000, ISO 353000, ISO 354000, ISO 355000, ISO 356000, ISO 357000, ISO 358000, ISO 359000, ISO 360000, ISO 361000, ISO 362000, ISO 363000, ISO 364000, ISO 365000, ISO 366000, ISO 367000, ISO 368000, ISO 369000, ISO 370000, ISO 371000, ISO 372000, ISO 373000, ISO 374000, ISO 375000, ISO 376000, ISO 377000, ISO 378000, ISO 379000, ISO 380000, ISO 381000, ISO 382000, ISO 383000, ISO 384000, ISO 385000, ISO 386000, ISO 387000, ISO 388000, ISO 389000, ISO 390000, ISO 391000, ISO 392000, ISO 393000, ISO 394000, ISO 395000, ISO 396000, ISO 397000, ISO 398000, ISO 399000, ISO 400000, ISO 401000, ISO 402000, ISO 403000, ISO 404000, ISO 405000, ISO 406000, ISO 407000, ISO 408000, ISO 409000, ISO 410000, ISO 411000, ISO 412000, ISO 413000, ISO 414000, ISO 415000, ISO 416000, ISO 417000, ISO 418000, ISO 419000, ISO 420000, ISO 421000, ISO 422000, ISO 423000, ISO 424000, ISO 425000, ISO 426000, ISO 427000, ISO 428000, ISO 429000, ISO 430000, ISO 431000, ISO 432000, ISO 433000, ISO 434000, ISO 435000, ISO 436000, ISO 437000, ISO 438000, ISO 439000, ISO 440000, ISO 441000, ISO 442000, ISO 443000, ISO 444000, ISO 445000, ISO 446000, ISO 447000, ISO 448000, ISO 449000, ISO 450000, ISO 451000, ISO 452000, ISO 453000, ISO 454000, ISO 455000, ISO 456000, ISO 457000, ISO 458000, ISO 459000, ISO



Product Applications: Fuel Tanks, Working Hoppers, General Cargo Hoppers


[illegible]

Installation Procedure Following The Installation Of Primary Hardware, Profile Brackets Are Used And Secured With Screws Below. This Method Facilitates Straightforward Installation And Secured Process.



CT-1 系列扣条 (木地板扣条) | CT-1 Profile Strip (Wooden Floor Trim)

型 号 / Model	CT-1, CT-1.4, CT-1.8, CT-2.1
规格尺寸 / Package Width	6mm, 14mm, 18mm, 21mm
长 度 / Length	2.7米/m
材 质 / Material	铝镁合金 / Aluminium Alloy
表面处理 / Surface Colour	多种工艺 颜色可选 / Multiple Finishes Available Colour Options Available
安装说明 / Installation Details	↓



产品应用: 地板, 墙脚过渡扣条

Product Application: Floor to wall Transition Trim




安装说明: 将扣条放入预先开好的槽中, 安装便捷, 施工迅速

Installation Procedure: Reserve Gaps For Subsequent Insertion Of Profiles, Covered With Glueless Sealant. This Facilitates Straightforward Installation And Groundwork Processes




CTR-1 地板调平垫扣条 | CTR-1 Floor Leveling Strip

型 号 / Model	CTR-1, CTR-1.5, CTR-2
规格尺寸 / Package Width	6mm, 15mm, 20mm
长 度 / Length	2.7米/m
材 质 / Material	铝镁合金 / Aluminium Alloy
表面处理 / Surface Colour	多种工艺 颜色可选 / Multiple Finishes Available Colour Options Available
安装说明 / Installation Details	↓



产品应用: 地板, 墙脚过渡扣条, 高低差扣条

Product Application: Floor to wall Transition Inlets Level Difference Inlets



安装说明: 将扣条放入预先开好的槽中, 安装便捷, 施工迅速

Installation Procedure: Reserve Gaps For Subsequent Insertion Of Profiles, Covered With Glueless Sealant. This Facilitates Straightforward Installation And Groundwork Processes



LHD- 地槽与地板夹 | LHD - Universal Floor Clip

型 号 Model	LHD11, LHD12
长度尺寸 Frontage Width	60mm, 40mm
长 度 Length	2.7米/m
材 质 Material	铝镁合金 Aluminum Alloy
表面颜色 Surface Colour	多种工艺 颜色可选 Multiple Processes Available Colour Options Available
安装说明 Installation Details	见下文



产品特点: 安装方便, 适用于各种地板与墙体之间的缝隙, 以及地板与地板之间的缝隙。

Product Application: Seamless Transition Between Floor and Wall Surface, and Bridging slight Differences For Various Materials including Wooden Flooring Tiles and Stone.



安装说明: 使用工具, 将地板与墙体, 地板与地板, 地板与地板, 地板与地板, 地板与地板。

Installation Procedure: Reserve Space, Install Profiles/With Saw Clips, Secure With Silicone Sealant. Installation In Straightforward and Streamlined.




TC-C 单边边扣条 | TC-C Single-sided Edge Trim (Wood Flooring)

型 号 Model	TC14, TC12, TC14, TC14, TC14
边扣条高度 Closure Height	60mm, 40mm, 60mm, 60mm, 60mm
长 度 Length	2.7米/m
材 质 Material	铝镁合金 Aluminum Alloy
表面颜色 Surface Colour	多种工艺 颜色可选 Multiple Processes Available Colour Options Available
安装说明 Installation Details	见下文



产品特点: 安装方便, 适用于各种地板与墙体之间的缝隙, 以及地板与地板之间的缝隙。

Product Application: Seamless Transition Between Floor and Wall Surface, and Bridging slight Differences For Various Materials including Wooden Flooring and Materials Such as Ceramic Tiles and Stone.



安装说明: 使用工具, 将地板与墙体, 地板与地板, 地板与地板, 地板与地板, 地板与地板。

Installation Procedure: Profiles Must Be Installed Concurrently With Primary Materials, Secured With Silicone Sealant. Installation Is Straightforward, Simplifying The Process.



F18

F18- 铝合金地板收边条 | F18 - Aluminium Alloy Floor Trim

型 号 (Model)	F18
收口高度 (Close Height)	20mm
长 度 (Length)	2.7米 (m)
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	多种工艺, 颜色可选 (Multiple finishes available. Colour options available)
安装附件 (Installation Details)	见图 (See Fig)



产品应用: 适用于 20mm 以上木地板, 实木地板 (Solid Wood Floor)

Product Application: Suitable For Transition From Co/Wooden Flooring And Tiles With A Thickness Of More Or Greater



安装说明: 需与基材材料施工, 先安装并固定好收边条, 再安装木地板, 实木地板 (Solid Wood Floor), 实木地板 (Solid Wood Floor)

Installation Procedure: Must Be Carried Out Consistently With Primary Materials. First Install The Clip on Fittings And Profiles, Then Subsequently Snap The Clip on Fittings into Place For Securing. Installation Is Straightforward And Streamlines The Process



F18

F18- 铝合金地板收边条 | F18 - Aluminium Alloy Floor Skirting

型 号 (Model)	F18
收口高度 (Close Height)	20mm
长 度 (Length)	2.7米 (m)
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	钛金, 银 (Titanium Gold, Matte Black)
安装附件 (Installation Details)	/



安装说明: 需与基材材料施工, 先安装并固定好收边条, 再安装木地板, 实木地板 (Solid Wood Floor), 实木地板 (Solid Wood Floor)

Installation Procedure: Must Be Carried Out Consistently With Primary Materials. First Install The Clip on Fittings And Profiles, Then Subsequently Snap The Clip on Fittings into Place For Securing. Installation Is Straightforward And Streamlines The Process

产品应用: 适用于木地板收边条, 实木地板, 实木地板 (Solid Wood Floor), 实木地板 (Solid Wood Floor)

Product Application: Aluminium Alloy Floor Skirting Strip. Base Can Be Secured With Screws Or Adhesive Glue. Height adjustable. Suitable For Wooden Flooring From Thick And Slender



FST

FST- 铝合金地板收边条 | FST - Aluminium Alloy Floor Skirting

型 号 (Model)	FST
规格尺寸 (Frontage Width)	20mm
长 度 (Length)	2.7米
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	银色, 黑色 (Titanium Gold, Matte Black)
安装说明 (Installation Details)	见



产品特点: 铝合金地板收边条, 高度可调节, 可安装于, 无缝拼接, 适用3mm以上地板

Product Application: Aluminium Alloy Floor Edging Strip Base Can Be Covered With Screws Or Adhesive Sealant. Height adjustable. Suitable For Wooden Floating Floor/Thick Or Dealer



安装说明: 需先安装好地板工头并留出安装收边条位置, 安装收边条, 无缝拼接

Installation Procedure: Must Be Carried Out Concurrently With Primary Materials. First Install The Clip on Fittings And Profiles, Then Subsequently Snap The Clip on Fittings into Place For Securing. Installation Is Straightforward And Streamlines The Process



FT


FT- 铝合金平面过渡条 | FT- Aluminium Alloy Flat Transition Strip

型 号 (Model)	FT
规格尺寸 (Frontage Width)	20mm
长 度 (Length)	2.7米
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	银色, 黑色 (Titanium Gold, Matte Black)
安装说明 (Installation Details)	见



产品特点: 铝合金地板收边条, 高度可调节, 可安装于, 无缝拼接, 适用3mm以上地板

Product Application: Aluminium Alloy Floor Edging Strip Base Can Be Covered With Screws Or Adhesive Sealant. Height adjustable. Suitable For Wooden Floating Floor/Thick Or Dealer



安装说明: 需先安装好地板工头并留出安装收边条位置, 安装收边条, 无缝拼接

Installation Procedure: Must Be Carried Out Concurrently With Main Materials. First Install The Clip on Fittings And Profiles, Then Subsequently Snap The Clip on Fittings into Place For Securing. Installation Is Straightforward And Streamlines The Process



LTPB - 铝合金地板平边条 | LTPB - Aluminium Alloy Floor Edging Board

型 号 / Model	LTPB-L, LTPB-M, LTPB-R
规格尺寸 / Frontage Width	10mm, 11mm, 12mm
长 度 / Length	2.7m
材 质 / Material	铝合金 / Aluminium Alloy
表面处理 / Surface Coating	拉丝 / 镜面 / 电镀 / Titanium Gold / Antique Bronze / Warm Black
安装规格 / Installation Details	1'



产品特点：铝合金材质强度高，耐腐蚀性强，环保健康。安装方便，高度可调，适用于各种地板厚度（10-12mm）。

Product Application: Aluminium Alloy Floor Edging Strip Can Be General With Various On Adhesive Insulation Height adjustable Suitable For Wooden Flooring 10-12mm Thick And Stone

安装说明：需与地板厚度相匹配，安装前先用砂纸打磨地板表面，确保平整。安装时，先将地板平边条卡在地板与墙面之间，然后用螺丝固定。

Installation Procedure: Must Be Careful Not To Damage With Water Materials. First Install The Clip on Floorings And Profiles, Then Subsequently Snap The Clip on Floorings Into Place For Securing. Installation Is Straightforward And Streamlines The Process.

全屋精细收口/场景应用

Precision Finishing Throughout The Home / Scenario Application

木地板收口应用

Application Of Wooden Floor Finishing





踏步台面系列 Stair Nosing & Countertop Series

适用于楼梯口、窗台边沿、墙脚、踢脚、窗框包角等金属材料过渡、包角、包边处理。施工便捷，耐久耐用，方便护理，效果美观。

Also Known As: Plinthe Building, Covering Tiles, Wall Panels, Paintwork, Rail Balustrade and Feature Walls
Transferring, Joining, And Connecting Functions: Straightforward Installation
Enduring: Appeals Easy Maintenance: Aesthetically Pleasing Results

www.lmcmetal.com




LTY - 踏步台面接口线 | LTY - Stair Tread Edge Trim

型 号 (Model)	LTY11, LTY111
接口高度 (Mounting Height)	24mm, 24.1mm
宽 度 (Length)	2.0 meters
材 质 (Material)	铝合金 (Aluminium Alloy)
表面处理 (Surface Colour)	多种工艺 颜色可选 (Multiple Finishes Available / Colour Options Available)
安装说明 (Corner Fitting)	安装方便 (Easy Installation) / Simplified Procedures



产品应用 - 楼梯踏步, 台面转角接口

Product Application (Stair Treads, Countertop/External Corner Trim)




安装说明: 台阶踏步与材料衔接处, 转角处, 台面, 窗框, 窗台, 窗台, 窗台

Installation Procedures: Profiles Must Be Installed Concurrently With Primary Materials, General Using The Following Installation Is Straightforward And Streamlined



LSGD- 樓梯踏步收口條 | LSGD - Stair Tread Finishing Strip

型 号 Model:	LSGDY13.1
收口高度 Closure Height:	12.5mm
长 度 Length:	3 米/3m
材 质 Material:	铝合金 Aluminium Alloy
表面颜色 Surface Colour:	钛金色 Titanium Gold / 黑色 Matte Black
安装说明 Installation Details:	↓



产品应用：楼梯收口，台阶级侧收口

Product Application: Stair Treads, Countertop External Corner Trim



安装说明：型材需与基材同时施工，嵌填密封胶，安装玻璃，填胶工单

Installation Procedure: Profiles Must Be Installed Concurrently With Primary Materials, Seamed Using The Adhesive. Installation Is Straightforward And Uncomplicated



LTV- 楼梯踏步条 | LTV - Stair Tread Anti-slip Strips

型 号 Model:	LTV0013
收口高度 Closure Height:	25mm
长 度 Length:	3 米/3m
材 质 Material:	铝合金 Aluminium Alloy
表面颜色 Surface Colour:	多种工艺 (多种可选) Multiple Finishes Available Colour Options Available
安装说明 Installation Details:	↓



产品应用：楼梯收口，台阶级侧收口

Product Application: Stair Treads, Countertop External Corner Trim



安装说明：型材需与基材同时施工，嵌填密封胶，安装玻璃，填胶工单

Installation Procedure: Profiles Must Be Installed Concurrently With Primary Materials, Seamed Using The Adhesive. Installation Is Straightforward And Uncomplicated



種 名 / Species:	山竹木
樹高(最大) / Maximum Height:	11 Meters
樹 皮 / Bark:	20cm/cm
樹 葉 / Leaves:	(細葉) <i>Chlorocardium oliveri</i>
果實(樹上) / Fruits/Gallies:	(樹上) <i>E. (Pithecellobium) / Multiple Pithless Gallies/Galls Available</i>
用途(樹皮) / Medicinal Benefits:	-



全厚精細收口/場景應用

Copyright © 2006 John Wiley & Sons, Ltd.

Figure 1

[illegible]

[illegible]

Sliding Applications For Wall Coverings Such As Tiles And Wall Panels
Compatible Corner Firms, Simplified Processing Steps, Straightforward Installation,
And Versatility Provide Results.

[illegible]

型 号 Model:	T6A70, T6A80, T6A90, T6A100, T6A120
接口类型 Interface Type(s):	HDMI, eSATA, FireWire, iSCSI, USB
背 景 Sample:	2.5 inches
材 质 Material:	铝合金 Aluminum Alloy
颜色选项 Surface Color(s):	标准(工厂)颜色选项 Multiple Factory Available Colors/Options Available
安装选项 Carrier Fit(s):	快速安装 Quick & Easy Installation / Simplified Procedures

[illegible]

Product Applications Catalog
Resins for Wall Materials, Cores
for Tiles, Wall Panels, Moldings
from About 1900



1. *Chlorophyll a* (Chl *a*)

2. *Chlorophyll b* (Chl *b*)

3. *Carotenoids*

4. *Xanthophylls*

5. *Phycobilins*

6. *Phaeophytins*

7. *Phaeopigments*

8. *Phaeoerythrin*

9. *Phaeo-*fucoxanthin**

10. *Phaeo-*peridinin**

11. *Phaeo-*zeaxanthin**

12. *Phaeo-*violaxanthin**

13. *Phaeo-*zeaxanthin**

14. *Phaeo-*zeaxanthin**

15. *Phaeo-*zeaxanthin**

16. *Phaeo-*zeaxanthin**

17. *Phaeo-*zeaxanthin**

18. *Phaeo-*zeaxanthin**

19. *Phaeo-*zeaxanthin**

20. *Phaeo-*zeaxanthin**

21. *Phaeo-*zeaxanthin**

22. *Phaeo-*zeaxanthin**

23. *Phaeo-*zeaxanthin**

24. *Phaeo-*zeaxanthin**

25. *Phaeo-*zeaxanthin**

26. *Phaeo-*zeaxanthin**

27. *Phaeo-*zeaxanthin**

28. *Phaeo-*zeaxanthin**

29. *Phaeo-*zeaxanthin**

30. *Phaeo-*zeaxanthin**

31. *Phaeo-*zeaxanthin**

32. *Phaeo-*zeaxanthin**

33. *Phaeo-*zeaxanthin**

34. *Phaeo-*zeaxanthin**

35. *Phaeo-*zeaxanthin**

36. *Phaeo-*zeaxanthin**

37. *Phaeo-*zeaxanthin**

38. *Phaeo-*zeaxanthin**

39. *Phaeo-*zeaxanthin**

40. *Phaeo-*zeaxanthin**

41. *Phaeo-*zeaxanthin**

42. *Phaeo-*zeaxanthin**

43. *Phaeo-*zeaxanthin**

44. *Phaeo-*zeaxanthin**

45. *Phaeo-*zeaxanthin**

46. *Phaeo-*zeaxanthin**

47. *Phaeo-*zeaxanthin**

48. *Phaeo-*zeaxanthin**

49. *Phaeo-*zeaxanthin**

50. *Phaeo-*zeaxanthin**

51. *Phaeo-*zeaxanthin**

52. *Phaeo-*zeaxanthin**

53. *Phaeo-*zeaxanthin**

54. *Phaeo-*zeaxanthin**

55. *Phaeo-*zeaxanthin**

56. *Phaeo-*zeaxanthin**

57. *Phaeo-*zeaxanthin**

58. *Phaeo-*zeaxanthin**

59. *Phaeo-*zeaxanthin**

60. *Phaeo-*zeaxanthin**

61. *Phaeo-*zeaxanthin**

62. *Phaeo-*zeaxanthin**

63. *Phaeo-*zeaxanthin**

64. *Phaeo-*zeaxanthin**

65. *Phaeo-*zeaxanthin**

66. *Phaeo-*zeaxanthin**

67. *Phaeo-*zeaxanthin**

68. *Phaeo-*zeaxanthin**

69. *Phaeo-*zeaxanthin**

70. *Phaeo-*zeaxanthin**

71. *Phaeo-*zeaxanthin**

72. *Phaeo-*zeaxanthin**

73. *Phaeo-*zeaxanthin**

74. *Phaeo-*zeaxanthin**

75. *Phaeo-*zeaxanthin**

76. *Phaeo-*zeaxanthin**

77. *Phaeo-*zeaxanthin**

78. *Phaeo-*zeaxanthin**

79. *Phaeo-*zeaxanthin**

80. *Phaeo-*zeaxanthin**

81. *Phaeo-*zeaxanthin**

82. *Phaeo-*zeaxanthin**

83. *Phaeo-*zeaxanthin**

84. *Phaeo-*zeaxanthin**

85. *Phaeo-*zeaxanthin**

86. *Phaeo-*zeaxanthin**

87. *Phaeo-*zeaxanthin**

88. *Phaeo-*zeaxanthin**

89. *Phaeo-*zeaxanthin**

90. *Phaeo-*zeaxanthin**

91. *Phaeo-*zeaxanthin**

92. *Phaeo-*zeaxanthin**

93. *Phaeo-*zeaxanthin**

94. *Phaeo-*zeaxanthin**

95. *Phaeo-*zeaxanthin**

96. *Phaeo-*zeaxanthin**

97. *Phaeo-*zeaxanthin**

98. *Phaeo-*zeaxanthin**

99. *Phaeo-*zeaxanthin**

100. *Phaeo-*zeaxanthin**

101. *Phaeo-*zeaxanthin**

102. *Phaeo-*zeaxanthin**

103. *Phaeo-*zeaxanthin**

104. *Phaeo-*zeaxanthin**

105. *Phaeo-*zeaxanthin**

106. *Phaeo-*zeaxanthin**

107. *Phaeo-*zeaxanthin**

108. *Phaeo-*zeaxanthin**

109. *Phaeo-*zeaxanthin**

110. *Phaeo-*zeaxanthin**

111. *Phaeo-*zeaxanthin**

112. *Phaeo-*zeaxanthin**

113. *Phaeo-*zeaxanthin**

114. *Phaeo-*zeaxanthin**

115. *Phaeo-*zeaxanthin**

116. *Phaeo-*zeaxanthin**

117. *Phaeo-*zeaxanthin**

118. *Phaeo-*zeaxanthin**

119. *Phaeo-*zeaxanthin**

120. *Phaeo-*zeaxanthin**

121. *Phaeo-*zeaxanthin**

122. *Phaeo-*zeaxanthin**

123. *Phaeo-*zeaxanthin**

124. *Phaeo-*zeaxanthin**

125. *Phaeo-*zeaxanthin**

126. *Phaeo-*zeaxanthin**

127. *Phaeo-*zeaxanthin**

128. *Phaeo-*zeaxanthin**

129. *Phaeo-*zeaxanthin**

130. *Phaeo-*zeaxanthin**

131. *Phaeo-*zeaxanthin**

132. *Phaeo-*zeaxanthin**

133. *Phaeo-*zeaxanthin**

134. *Phaeo-*zeaxanthin**

135. *Phaeo-*zeaxanthin**

136. *Phaeo-*zeaxanthin**

137. *Phaeo-*zeaxanthin**

138. *Phaeo-*zeaxanthin**

139. *Phaeo-*zeaxanthin**

140. *Phaeo-*zeaxanthin**

141. *Phaeo-*zeaxanthin**

142. *Phaeo-*zeaxanthin**

143. *Phaeo-*zeaxanthin**

144. *Phaeo-*zeaxanthin**

145. *Phaeo-*zeaxanthin**

146. *Phaeo-*zeaxanthin**

147. *Phaeo-*zeaxanthin**

148. *Phaeo-*zeaxanthin**

149. *Phaeo-*zeaxanthin**

150. *Phaeo-*zeaxanthin**

151. *Phaeo-*zeaxanthin**

152. *Phaeo-*zeaxanthin**

153. *Phaeo-*zeaxanthin**

154. *Phaeo-*zeaxanthin**

155. *Phaeo-*zeaxanthin**

156. *Phaeo-*zeaxanthin**

157. *Phaeo-*zeaxanthin**

158. *Phaeo-*

1. **Introduction**
 2. **Background**
 3. **Methodology**
 4. **Results**
 5. **Discussion**
 6. **Conclusion**
 7. **References**
 8. **Appendix**
 9. **Index**
 10. **Table of Contents**
 11. **Figure 1**
 12. **Figure 2**
 13. **Figure 3**
 14. **Figure 4**
 15. **Figure 5**
 16. **Figure 6**
 17. **Figure 7**
 18. **Figure 8**
 19. **Figure 9**
 20. **Figure 10**
 21. **Figure 11**
 22. **Figure 12**
 23. **Figure 13**
 24. **Figure 14**
 25. **Figure 15**
 26. **Figure 16**
 27. **Figure 17**
 28. **Figure 18**
 29. **Figure 19**
 30. **Figure 20**
 31. **Figure 21**
 32. **Figure 22**
 33. **Figure 23**
 34. **Figure 24**
 35. **Figure 25**
 36. **Figure 26**
 37. **Figure 27**
 38. **Figure 28**
 39. **Figure 29**
 40. **Figure 30**
 41. **Figure 31**
 42. **Figure 32**
 43. **Figure 33**
 44. **Figure 34**
 45. **Figure 35**
 46. **Figure 36**
 47. **Figure 37**
 48. **Figure 38**
 49. **Figure 39**
 50. **Figure 40**
 51. **Figure 41**
 52. **Figure 42**
 53. **Figure 43**
 54. **Figure 44**
 55. **Figure 45**
 56. **Figure 46**
 57. **Figure 47**
 58. **Figure 48**
 59. **Figure 49**
 60. **Figure 50**
 61. **Figure 51**
 62. **Figure 52**
 63. **Figure 53**
 64. **Figure 54**
 65. **Figure 55**
 66. **Figure 56**
 67. **Figure 57**
 68. **Figure 58**
 69. **Figure 59**
 70. **Figure 60**
 71. **Figure 61**
 72. **Figure 62**
 73. **Figure 63**
 74. **Figure 64**
 75. **Figure 65**
 76. **Figure 66**
 77. **Figure 67**
 78. **Figure 68**
 79. **Figure 69**
 80. **Figure 70**
 81. **Figure 71**
 82. **Figure 72**
 83. **Figure 73**
 84. **Figure 74**
 85. **Figure 75**
 86. **Figure 76**
 87. **Figure 77**
 88. **Figure 78**
 89. **Figure 79**
 90. **Figure 80**
 91. **Figure 81**
 92. **Figure 82**
 93. **Figure 83**
 94. **Figure 84**
 95. **Figure 85**
 96. **Figure 86**
 97. **Figure 87**
 98. **Figure 88**
 99. **Figure 89**
 100. **Figure 90**
 101. **Figure 91**
 102. **Figure 92**
 103. **Figure 93**
 104. **Figure 94**
 105. **Figure 95**
 106. **Figure 96**
 107. **Figure 97**
 108. **Figure 98**
 109. **Figure 99**
 110. **Figure 100**
 111. **Figure 101**
 112. **Figure 102**
 113. **Figure 103**
 114. **Figure 104**
 115. **Figure 105**
 116. **Figure 106**
 117. **Figure 107**
 118. **Figure 108**
 119. **Figure 109**
 120. **Figure 110**
 121. **Figure 111**
 122. **Figure 112**
 123. **Figure 113**
 124. **Figure 114**
 125. **Figure 115**
 126. **Figure 116**
 127. **Figure 117**
 128. **Figure 118**
 129. **Figure 119**
 130. **Figure 120**
 131. **Figure 121**
 132. **Figure 122**
 133. **Figure 123**
 134. **Figure 124**
 135. **Figure 125**
 136. **Figure 126**
 137. **Figure 127**
 138. **Figure 128**
 139. **Figure 129**
 140. **Figure 130**
 141. **Figure 131**
 142. **Figure 132**
 143. **Figure 133**
 144. **Figure 134**
 145. **Figure 135**
 146. **Figure 136**
 147. **Figure 137**
 148. **Figure 138**
 149. **Figure 139**
 150. **Figure 140**
 151. **Figure 141**
 152. **Figure 142**
 153. **Figure 143**
 154. **Figure 144**
 155. **Figure 145**
 156. **Figure 146**
 157. **Figure 147**
 158. **Figure 148**
 159. **Figure 149**
 160. **Figure 150**
 161. **Figure 151**
 162. **Figure 152**
 163. **Figure 153**
 164. **Figure 154**
 165. **Figure 155**
 166. **Figure 156**
 167. **Figure 157**
 168. **Figure 158**
 169. **Figure 159**
 170. **Figure 160**
 171. **Figure 161**
 172. **Figure 162**
 173. **Figure 163**
 174. **Figure 164**
 175. **Figure 165**
 176. **Figure 166**
 177. **Figure 167**
 178. **Figure 168**
 179. **Figure 169**
 180. **Figure 170**
 181. **Figure 171**
 182. **Figure 172**
 183. **Figure 173**
 184. **Figure 174**
 185. **Figure 175**
 186. **Figure 176**
 187. **Figure 177**
 188. **Figure 178**
 189. **Figure 179**
 190. **Figure 180**
 191. **Figure 181**
 192. **Figure 182**
 193. **Figure 183**
 194. **Figure 184**
 195. **Figure 185**
 196. **Figure 186**
 197. **Figure 187**
 198. **Figure 188**
 199. **Figure 189**
 200. **Figure 190**
 201. **Figure 191**
 202. **Figure 192**
 203. **Figure 193**
 204. **Figure 194**
 205. **Figure 195**
 206. **Figure 196**
 207. **Figure 197**
 208. **Figure 198**
 209. **Figure 199**
 210. **Figure 200**
 211. **Figure 201**
 212. **Figure 202**
 213. **Figure 203**
 214. **Figure 204**
 215. **Figure 205**
 216. **Figure 206**
 217. **Figure 207**
 218



11. *Journal of the American Medical Association*, 2000; 283: 2686-2692.

高 (度) Height	Höhe, Höhen
高(度) Chinese Height	álgom, álgom
度 (度) Length	Länge
度 (度) Material	Material (Edelmaterial) Stoff
度(度) Surface Color	表面(度) 表面(度) Multiple Possible Available Colors Options Available
度(度) Corner Pitting	度(度) Key Installation, Simplified Presentation



1000



Abstract




Abstract



Abstract



Abstract



Product Applications: Mining
Household (Wall Removers, Sinks,
etc.); Ware, Mill Remedy, Millstones;
Iron, Steel Pipes.

Product Applications: Mining
Household (Wall Removers, Sinks,
etc.); Ware, Mill Remedy, Millstones;
Iron, Steel Pipes.

[illegible][illegible][illegible]

Abstract



1. **Introduction**
 2. **Methodology**
 3. **Results**
 4. **Discussion**
 5. **Conclusion**
 6. **References**
 7. **Appendix**
 8. **Index**
 9. **Glossary**
 10. **Notes**
 11. **Footnotes**
 12. **Endnotes**
 13. **Supplementary Material**
 14. **Tables**
 15. **Figures**
 16. **Equations**
 17. **Formulas**
 18. **Diagrams**
 19. **Charts**
 20. **Graphs**
 21. **Tables**
 22. **Figures**
 23. **Equations**
 24. **Formulas**
 25. **Diagrams**
 26. **Charts**
 27. **Graphs**
 28. **Tables**
 29. **Figures**
 30. **Equations**
 31. **Formulas**
 32. **Diagrams**
 33. **Charts**
 34. **Graphs**
 35. **Tables**
 36. **Figures**
 37. **Equations**
 38. **Formulas**
 39. **Diagrams**
 40. **Charts**
 41. **Graphs**
 42. **Tables**
 43. **Figures**
 44. **Equations**
 45. **Formulas**
 46. **Diagrams**
 47. **Charts**
 48. **Graphs**
 49. **Tables**
 50. **Figures**
 51. **Equations**
 52. **Formulas**
 53. **Diagrams**
 54. **Charts**
 55. **Graphs**
 56. **Tables**
 57. **Figures**
 58. **Equations**
 59. **Formulas**
 60. **Diagrams**
 61. **Charts**
 62. **Graphs**
 63. **Tables**
 64. **Figures**
 65. **Equations**
 66. **Formulas**
 67. **Diagrams**
 68. **Charts**
 69. **Graphs**
 70. **Tables**
 71. **Figures**
 72. **Equations**
 73. **Formulas**
 74. **Diagrams**
 75. **Charts**
 76. **Graphs**
 77. **Tables**
 78. **Figures**
 79. **Equations**
 80. **Formulas**
 81. **Diagrams**
 82. **Charts**
 83. **Graphs**
 84. **Tables**
 85. **Figures**
 86. **Equations**
 87. **Formulas**
 88. **Diagrams**
 89. **Charts**
 90. **Graphs**
 91. **Tables**
 92. **Figures**
 93. **Equations**
 94. **Formulas**
 95. **Diagrams**
 96. **Charts**
 97. **Graphs**
 98. **Tables**
 99. **Figures**
 100. **Equations**
 101. **Formulas**
 102. **Diagrams**
 103. **Charts**
 104. **Graphs**
 105. **Tables**
 106. **Figures**
 107. **Equations**
 108. **Formulas**
 109. **Diagrams**
 110. **Charts**
 111. **Graphs**
 112. **Tables**
 113. **Figures**
 114. **Equations**
 115. **Formulas**
 116. **Diagrams**
 117. **Charts**
 118. **Graphs**
 119. **Tables**
 120. **Figures**
 121. **Equations**
 122. **Formulas**
 123. **Diagrams**
 124. **Charts**
 125. **Graphs**
 126. **Tables**
 127. **Figures**
 128. **Equations**
 129. **Formulas**
 130. **Diagrams**
 131. **Charts**
 132. **Graphs**
 133. **Tables**
 134. **Figures**
 135. **Equations**
 136. **Formulas**
 137. **Diagrams**
 138. **Charts**
 139. **Graphs**
 140. **Tables**
 141. **Figures**
 142. **Equations**
 143. **Formulas**
 144. **Diagrams**
 145. **Charts**
 146. **Graphs**
 147. **Tables**
 148. **Figures**
 149. **Equations**
 150. **Formulas**
 151. **Diagrams**
 152. **Charts**
 153. **Graphs**
 154. **Tables**
 155. **Figures**
 156. **Equations**
 157. **Formulas**
 158. **Diagrams**
 159. **Charts**
 160. **Graphs**
 161. **Tables**
 162. **Figures**
 163. **Equations**
 164. **Formulas**
 165. **Diagrams**
 166. **Charts**
 167. **Graphs**
 168. **Tables**
 169. **Figures**
 170. **Equations**
 171. **Formulas**
 172. **Diagrams**
 173. **Charts**
 174. **Graphs**
 175. **Tables**
 176. **Figures**
 177. **Equations**
 178. **Formulas**
 179. **Diagrams**
 180. **Charts**
 181. **Graphs**
 182. **Tables**
 183. **Figures**
 184. **Equations**
 185. **Formulas**
 186. **Diagrams**
 187. **Charts**
 188. **Graphs**
 189. **Tables**
 190. **Figures**
 191. **Equations**
 192. **Formulas**
 193. **Diagrams**
 194. **Charts**
 195. **Graphs**
 196. **Tables**
 197. **Figures**
 198. **Equations**
 199. **Formulas**
 200. **Diagrams**
 201. **Charts**
 202. **Graphs**
 203. **Tables**
 204. **Figures**
 205. **Equations**
 206. **Formulas**
 207. **Diagrams**
 208. **Charts**
 209. **Graphs**
 210. **Tables**
 211. **Figures**
 212. **Equations**
 213. **Formulas**
 214. **Diagrams**
 215. **Charts**
 216. **Graphs**
 217. **Tables**
 218. **Figures**
 219. **Equations**
 220. **Formulas**
 221. **Diagrams**
 222. **Charts**
 223. **Graphs**
 224. **Tables**
 225. **Figures**
 226. **Equations**
 227. **Formulas**
 228. **Diagrams**
 229. **Charts**
 230. **Graphs**
 231. **Tables**
 232. **Figures**
 233. **Equations**
 234. **Formulas**
 235. **Diagrams**
 236. **Charts**
 237. **Graphs**
 238. **Tables**
 239. **Figures**
 240. **Equations**
 241. **Formulas**
 242. **Diagrams**
 243. **Charts**
 244. **Graphs**
 245. **Tables**
 246. **Figures**
 247. **Equations**
 248. **Formulas**
 249. **Diagrams**
 250. **Charts**
 251. **Graphs**
 252.



© 2000 Blackwell Science Ltd



Copyright © 2004 John Wiley & Sons, Ltd.



Figure 1

Year	1990	1991	1992	1993	1994
1990	1991	1992	1993	1994	1995

Product Application: Skirting Boards, Re-Wall Materials, Cash Jo Tiles, Wall Panels, Wallcoverings, and More



【关键词】 网络教育; 网络课程; 网络资源; 网络教学; 网络学习; 网络支持

Installation Precautions: The substrate must be thoroughly cleaned, install the clip fittings and rear clamping (Anilin). Installation is straightforward, simplifying the process.




R111 - 铝合金卡扣踢脚线 | R111 - Aluminium Alloy Snap-fit Skirting Board

型 号 (Model)	R111
接口高度 (Crease Height)	12mm
长 度 (Length)	2.1m/6ft
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	多种工艺, 颜色可选 (Multiple Finishes Available/Colour Options Available)
安装说明 (Installation Details)	1



产品应用: 踢脚线, 墙脚, 浴室等墙面材料收边收口

Product Application: Skirting Boards For Wall Materials Such As Tiles, Wall Panels, Wallcoverings, And More




安装说明: 提前准备好基层, 安装卡扣, 将型材 安装到位, 压实压紧

Installation Procedure: The Substrate Must Be Thoroughly Cleared, Install The Clip Fittings And Then Clamping Profiles. Installation Is Straightforward, Simplifying The Process




R11 - 超窄弧形踢脚线 | R11 - Ultra-narrow Curved Skirting Board

型 号 (Model)	R11C16, R11C18
接口高度 (Crease Height)	12mm, 18mm
长 度 (Length)	2.1m/6ft
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	多种工艺, 颜色可选 (Multiple Finishes Available/Colour Options Available)
安装说明 (Corner Fitting)	快速安装, 简化工序 (Easy Installation, Simplified Procedures)



产品应用: 浴室等墙面

Product Application: Ultra-narrow Curved Skirting Board



安装说明: 提前准备好基层材料, 提前安装好, 快速安装, 简化工序

Installation Procedure: Profiles Must Be Installed Concurrently With Primary Materials, Installed Using The Adhesive Installation Is Straightforward And Convenient




BAS - 极简卡扣隐藏型 | BAS - Minimalist Grip-In Skirting Board

型 号 (Model)	BAS01, BAS02, BAS03, BAS04
嵌口高度 (Channel Height)	8mm, 10mm, 10mm, 10mm
长 度 (Length)	2.1m/2m
材 质 (Material)	铝合金 (Aluminium Alloy)
表面处理 (Surface Colour)	多种工艺颜色可选 (Multiple Finishes Available/Colour Options Available)
安装结构 (Corner Fitting)	快装方便, 施工简单 (Easy Installation, Simplified Procedures)



产品应用: 踢脚, 墙边, 墙角, 墙角等装饰线条的应用

Product Application: Skirting Boards For Wall Materials Such As Tiles, Wall Panels, Wallcoverings, And Paint.



安装流程: 测量墙面尺寸并标记, 安装卡扣, 固定卡扣, 安装踢脚, 施工完成

Installation Procedure: The Substrate Must Be Thoroughly Cleared, Install The Clip Fittings And Nail Clamping Profiles. Installation Is Straightforward, Simplifying The Process.




TRG - 内嵌弧形平口隐藏型 | TRG - Embedded Curved Edge Flush Skirting Board

型 号 (Model)	TRG01, TRG02, TRG03, TRG04
嵌口高度 (Channel Height)	10mm, 10mm, 10mm, 10mm
长 度 (Length)	2.1m/2m
材 质 (Material)	铝合金 (Aluminium Alloy)
表面处理 (Surface Colour)	多种工艺颜色可选 (Multiple Finishes Available/Colour Options Available)
安装结构 (Corner Fitting)	快装方便, 施工简单 (Easy Installation, Simplified Procedures)



产品应用: 踢脚, 墙边等装饰线条的应用

Product Application: Skirting Boards For Wall Materials Such As Tiles And Wall Panels.



安装流程: 测量墙面尺寸并标记, 安装卡扣, 固定卡扣, 安装踢脚, 施工完成

Installation Procedure: Remove The Main Components First, Then Slot In The Profiles. Adhesive Bonding Eliminates The Need For Nails, Ensuring Straightforward Installation And Streamlined Procedures.




LAG - 超薄踢脚线 | LAG - ultra-thin skirting board

型 号 (Model)	LAG027, LAG030, LAG040
接口高度 (Crease Height)	25mm, 30mm, 40mm
长 度 (Length)	2.4m/8ft
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	多种工艺, 颜色可选 (Multiple Finishes Available/Colour Options Available)
安装结构 (Corner Fixing)	安装方便, 施工简单 (Easy Installation, Simplified Procedures)



产品应用: 瓷砖, 地板, 墙体装饰等任何墙面材料

Product Application: External Skirting Boards For Wall Materials Such As Tiles, Floors, Wall Panels, Etc



安装说明: 基层需保持平整, 墙面干净, 无裂缝, 接口处用胶, 安装便捷, 施工简单

Installation Procedure: The Substrate Must Be Thoroughly Cleaned And Ensured To Be Level And Cracks. Secure Using Screws/Adhesives And Adhesive Without Nails. Installation Is Straightforward And Streamlined




BCS - 方形卡扣踢脚线 | BCS - Square Clip-on Skirting Board

型 号 (Model)	BCS040, BCS050
接口高度 (Crease Height)	40mm, 50mm
长 度 (Length)	2.4m/8ft
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	多种工艺, 颜色可选 (Multiple Finishes Available/Colour Options Available)
安装结构 (Installation Details)	1'



产品应用: 瓷砖, 地板, 墙体装饰等任何墙面材料

Product Application: External Skirting Boards For Wall Materials Such As Tiles, Floors, Wall Panels, Etc



安装说明: 基层需保持平整, 墙面干净, 无裂缝, 接口处用胶, 安装便捷, 施工简单

Installation Procedure: The Substrate Must Be Thoroughly Cleaned And Ensured To Be Level And Cracks. Secure Using The Clip-Rings And Rear Clamping Profiles. Installation Is Straightforward Simplifying The Process



AC2-40

AC2 - 铝金属内嵌式密封条 | AC2 - Aluminium Alloy Plastic Head Skirting Board With Integrated Snap-In Features

型 号 (Model)	AC240
嵌口高度 (Channel Height)	25mm
长 度 (Length)	2.4m/8ft
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	多种工艺, 颜色可选 (Multiple Finishes Available/Colour Options Available)
安装说明 (Installation Details)	1



产品号: 854, 855, 856, 857, 858, 859, 860, 861, 862, 863, 864, 865, 866, 867, 868, 869, 870, 871, 872, 873, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 898, 899, 900, 901, 902, 903, 904, 905, 906, 907, 908, 909, 910, 911, 912, 913, 914, 915, 916, 917, 918, 919, 920, 921, 922, 923, 924, 925, 926, 927, 928, 929, 930, 931, 932, 933, 934, 935, 936, 937, 938, 939, 940, 941, 942, 943, 944, 945, 946, 947, 948, 949, 950, 951, 952, 953, 954, 955, 956, 957, 958, 959, 960, 961, 962, 963, 964, 965, 966, 967, 968, 969, 970, 971, 972, 973, 974, 975, 976, 977, 978, 979, 980, 981, 982, 983, 984, 985, 986, 987, 988, 989, 990, 991, 992, 993, 994, 995, 996, 997, 998, 999, 1000

Product Application: Snap-In Skirting Boards For Embedding Within Wall Materials Such As Tiles, Plaster Wall Panels, Etc.



安装说明: 确保墙面开槽平整, 安装牢固, 密封良好, 安装便捷, 施工简单。

Installation Procedure: The Substrate Must Be Thoroughly Cleaned. Install The Clip Fixings And Rail Clamping Profiles. Installation Is Straightforward, Simplifying The Process.



CTL - 内嵌 T 字铝密封条 | CTL - Embedded T-shaped Skirting Board

型 号 (Model)	CTL10, CTL20, CTL30, CTL40
嵌口高度 (Channel Height)	10mm, 20mm, 30mm, 40mm
长 度 (Length)	2.4m/8ft
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	多种工艺, 颜色可选 (Multiple Finishes Available/Colour Options Available)
安装说明 (Installation Details)	安装便捷, 施工简单 (Easy Installation, Simplified Procedures)



产品号: 854, 855, 856, 857, 858, 859, 860, 861, 862, 863, 864, 865, 866, 867, 868, 869, 870, 871, 872, 873, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 898, 899, 900, 901, 902, 903, 904, 905, 906, 907, 908, 909, 910, 911, 912, 913, 914, 915, 916, 917, 918, 919, 920, 921, 922, 923, 924, 925, 926, 927, 928, 929, 930, 931, 932, 933, 934, 935, 936, 937, 938, 939, 940, 941, 942, 943, 944, 945, 946, 947, 948, 949, 950, 951, 952, 953, 954, 955, 956, 957, 958, 959, 960, 961, 962, 963, 964, 965, 966, 967, 968, 969, 970, 971, 972, 973, 974, 975, 976, 977, 978, 979, 980, 981, 982, 983, 984, 985, 986, 987, 988, 989, 990, 991, 992, 993, 994, 995, 996, 997, 998, 999, 1000

Product Application: Recession Skirting Boards For Wall Materials Such As Tiles And Wall Panels



安装说明: 墙面开槽, 密封良好, 施工简单, 安装便捷, 施工简单。

Installation Procedure: Remove The Main Materials First, Then Slot In The Profiles. Adhesive Bonding Eliminates The Need For Nails, Ensuring Straightforward Installation And Seamless Processes.

[illegible]

Abstract



1000



Table 1

[illegible]

Product Identification: Research Chemicals Inc. 100 Wall Street, Suite 100, New York, NY 10038

[illegible]

Installation Procedures: Covers The Main Materials First, Then
 Shows The Proper Substrate Bonding Illustrates The Next
 Steps, Including Straightening And Securing The
 Material.



材 号 (Material):	16AL20-8
材 重 (Gross Weight):	250mm
材 长 (Length):	2.600mm
材 质 (Material):	铝 合金 (Aluminum Alloy)
材 料 号 (Surface Color):	银 色 (Silver) / 黑色 (Black) / 蓝色 (Blue) / 白色 (White) / 黄色 (Yellow) / 绿色 (Green) / 红色 (Red) / 紫色 (Purple) / 棕色 (Brown) / 灰色 (Gray) / 透明 (Transparent) / 其他 (Other)
材 料 号 (Material Grade):	2



Product Description: Unpublished Working Draft for Wall Research Book by The Great Wall Project, Spring 2009. Item

[illegible]

Installation/Preparation: First/Second Year High School, Reserve Class According To The Drawings, And For Using Nail Gun Make sure about Minimum/Maximum Installation In Neighbored wall And Foundation



CTPC - 嵌墙内嵌踢脚线 | CTPC - Plaster-embedded Skirting Board

型 号 (Model)	CINCO, CINCO, CINCO
嵌墙高度 (Channel Height)	20mm, 30mm, 40mm
长 度 (Length)	2.00m
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	多种工艺颜色可选 (Multiple Finishes Available Colour Options Available)
安装结构 (Corner Fixing)	预埋安装, 简化工艺 Pre-embed Installation, Simplified Procedures



产品应用：嵌墙内嵌踢脚线，简化工艺



产品应用：嵌墙内嵌踢脚线，简化工艺




产品应用：嵌墙内嵌踢脚线，简化工艺



产品应用：嵌墙内嵌踢脚线，简化工艺

Installation Procedure: Prepare The Plasterboard Substrate, Secure The Profile With A Nail Gun, Adhere The Plastering Mesh, apply The Skirt Coat



PLU-C - 嵌墙内嵌踢脚线 | PLU-C Type Plasterboard Embedded Skirting Board

型 号 (Model)	PLU-C20, PLU-C30, PLU-C40
嵌墙高度 (Channel Height)	20mm, 30mm, 40mm Natural Finish Surface May Be Covered With Simulation Film
长 度 (Length)	2.00m
材 质 (Material)	铝合金 (Aluminium Alloy)
表面颜色 (Surface Colour)	多种工艺颜色可选 (Multiple Finishes Available Colour Options Available)
安装结构 (Installation Details)	预埋安装, 简化工艺 Pre-embed Installation, Simplified Procedures




产品应用：嵌墙内嵌踢脚线，简化工艺

Installation Procedure: The Profile Must Be Pre-embedded In The Junctions With Plasterboard, Fill With Special-fast Joint Compound And After Plastering Mesh



材 料 (Material):	PLG-100, PLG-200, PLG-300
厚度 (Thickness):	厚度 (Thickness): 20mm, Natural mineral surface layer for coated with Emulsion Paint
长 度 (Length):	
材 质 (Material):	铝 (Aluminum alloy)
表面处理 (Surface Color):	银白色 (可任意颜色), 铝 (Natural Aluminum/Ready for Painting), Matt Black
安装 (Installation Details):	见



Product Identification: *Antony and Cleopatra*, with Kenneth S. Gougeon, Books and Theatre Series in Expanded Edition



Installation Procedure: The Profile Must Be Pre-Installed In The Junction With Mainboard. After With Specialized Joint Command (and With Precision Joint).



型 号 (Model)	ATN-20, ATN-30, ATN-50
总长度 (Overall Length)	20mm, 30mm, 40mm
材 质 (Material)	钛合金 (Titanium Alloy)
表面处理 (Surface Coating)	阳极氧化 (Anodized) / Hydroxy-Fluorine Acetate Coating-Optional Acetate
包装规格 (Carrier Pkging)	按图三显示 (By Installation, Simplified Procedures)



Product Development, Marketing, Finance, Research, and Sales, and the following are the names of the individuals who are responsible for each of these functions:



Installation/Preparation: Pre-drill holes. The main material, however, cuts according to the drawings, and fits using nail then adhesive and silicone caulk. Installation is straightforward and convenient.



CTPLE - 内嵌式石膏踢脚线 | CTPLE - Embedded Plaster Skirting Board

型 号 (Model)	CTPLE, CTPLE30, CTPLE40
槽口高度 (Groove Height)	20mm, 30mm, 40mm
长 度 (Length)	1.00m
材 质 (Material)	铝镁合金 (Aluminum Alloy)
表面处理 (Surface Colour)	多种工艺 颜色可选 (Multiple Finishes Available Colour Options Available)
安装结构 (Corner Fitting)	安装方便, 施工简单 (Easy Installation, Simplified Procedures)



产品应用: 瓷砖, 墙面板材料等的大面积应用, 方便施工和安装

Product Application: Embedded Skirting Boards For Wall Materials (Such As Tiles And Wall Panels) Calling Corner Times



安装说明: 在墙面上时, 将踢脚线对准位置, 然后, 将踢脚线, 安装到位, 施工简单

Installation Procedure: First Secure The Main Materials, Remove Bats According To The Drawings And For Using Nail Gun Additionally Also Use One System Installation Is Straightforward And Simplified



BPLG - 内嵌式光源踢脚线 | BPLG - Embedded Illuminated Skirting Board

型 号 (Model)	BPLG
槽口高度 (Groove Height)	20mm
长 度 (Length)	2.00m
材 质 (Material)	铝镁合金 (Aluminum Alloy)
表面处理 (Surface Colour)	多种工艺 颜色可选 (Multiple Finishes Available Colour Options Available)
安装结构 (Corner Fitting)	安装方便, 施工简单 (Easy Installation, Simplified Procedures)



产品应用: 瓷砖, 墙面板材料等的大面积应用, 方便施工和安装

Product Application: Recessed Illuminated Skirting Boards For Wall Materials (Such As Tiles And Wall Panels) Calling Corner Times



安装说明: 踢脚线安装于墙面, 安装牢固, 施工简单, 安装方便, 施工简单

Installation Procedure: The Substrate Must Be Thoroughly Cleaned, Install The Clip Fixings And Nail Clamping Profiles. Installation Is Straightforward Simplifying The Process



Tid - 内嵌式翻灯踢脚线 | Tid - Recessed Downlight Skirting Board

型 号 / Model	TL040-A, TL040-B
槽口宽度 / Closure Height	40mm, 60mm
长 度 / Length	1.00m
材 质 / Material	铝合金 / Aluminium Alloy
表面处理 / Surface Colour	多种工艺 多种可选 / Multiple Finishes Available Colour Options Available
安装结构 / Corner Fitting	安装方便, 施工简单 / Easy Installation, Simplified Procedures



产品应用: 踢灯, 暗灯等暗装式踢灯式踢脚线, 内嵌式踢灯

Product Application: Recessed/Illuminated Skirting Boards For Wall Materials Such As Tiles and Wall Panels Getting Corner Fittings



安装步骤: 先固定主材, 再固定角码, 最后, 用钉无钉胶, 完成安装, 施工简单

Installation Procedure: First Secure The Main Materials, Secure Ends According To The Drawings, And Fix Using Nail Free Adhesive And Silicone Sealants. Installation Is Straightforward And Streamlined



TLSD - 外挂 / 内嵌踢脚线 | TLSD - Surface-mounted / Recessed Skirting Boards

型 号 / Model	TL050A, TL050B
槽口宽度 / Closure Height	40mm, 60mm
长 度 / Length	1.00m
材 质 / Material	铝合金 / Aluminium Alloy
表面处理 / Surface Colour	多种工艺 多种可选 / Multiple Finishes Available Colour Options Available
安装结构 / Corner Fitting	安装方便, 施工简单 / Easy Installation, Simplified Procedures



产品应用: 踢灯, 暗灯等暗装式踢灯式踢脚线, 内嵌式踢灯

Product Application: Internal/Internal Skirting Boards For Wall Materials Such As Tiles and Wall Panels Getting Corner Fittings



安装步骤: 先固定主材, 再固定角码, 最后, 用钉无钉胶, 完成安装, 施工简单

Installation Procedure: First Secure The Main Materials, Secure Ends According To The Drawings, And Fix Using Nail Free Adhesive And Silicone Sealants. Installation Is Straightforward And Streamlined



CTD- 内嵌发光踢脚线 | CTD- Embedded Illuminated Skirting Board

型 号 (Model)	CTD01
槽口高度 (Channel Height)	40mm
长 度 (Length)	1.00m
材 质 (Material)	铝型材 (Aluminum Alloy)
表面处理 (Surface Colour)	多种工艺 颜色可选 (Multiple Finishes Available Colour Options Available)
安装结构 (Corner Fitting)	安装方便, 简化工艺 (Easy Installation, Simplified Procedures)



产品应用: 踢脚、装饰等铝型材内嵌式踢脚线, 内嵌LED灯条

Product Application: Embedded Skirting Boards For Wall Materials/Arch-In-Tile and Wall Panels/Glazing Corner Firms



安装说明: 内嵌LED灯条, 使用铝型材角条, 扣盖, 安装踢脚线, 安装方便, 简化工艺

Installation Procedure: First Remove The Main Materials, Remove Gels According To The Drawings, And Fix Using Nail-free Adhesive And Silicone Sealant. Installation Is Straightforward And Groundwork



TCST01

TCST- 超薄踢脚线 | TCST- Ultra-thin Skirting Board

型 号 (Model)	TCST01
槽口高度 (Channel Height)	20mm
长 度 (Length)	1.00m
材 质 (Material)	铝型材 (Aluminum Alloy)
表面处理 (Surface Colour)	多种工艺 颜色可选 (Multiple Finishes Available Colour Options Available)
安装结构 (Corner Fitting)	安装方便, 简化工艺 (Easy Installation, Simplified Procedures)



产品应用: 踢脚、装饰等铝型材

Product Application: Ultra-thin Skirting Boards For Conventional Doors



安装说明: 踢脚线铝型材, 使用铝型材角条, 扣盖, 安装踢脚线, 安装方便, 简化工艺

Installation Procedure: The Substrate Must Be Thoroughly Cleaned And Ensured To Be Level And Straight. Remove Using Silicone Sealant And Adhesive Without Nails. Installation Is Straightforward And Groundwork



LED 收口系列 Led Profile Series

覆盖室内、墙面等材料的边缘，隐藏LED光源以应用
将灯光与收口完美结合，一个型材解决两个问题需要

Application Of Luminous Trim For Flooring And Wall Surfaces Covered With Materials Such As Tiles And Wall Panels.

Seamlessly Integrating Illumination With Edging, A Single Profile Fulfills Dual Functional Requirements.

www.lmcmetal.com



LYD- 暗装收口型材 | LYD- Corner Trim Light Strip

型 号 (Model)	LYD-01
槽口高度 (Groove Height)	10.4mm
长 度 (Length)	3.000m
材 质 (Material)	铝合金 (Aluminum Alloy)
表面处理 (Surface Colour)	多种工艺 多种可选 (Multiple Finishes, Available Colour Options, Available)
安装结构 (Corner Fitting)	安装方便，简化工序 (Easy Installation, Simplified Procedures)



产品特点：(1) 集成化设计，将LED光源与收口型材完美结合，实现照明与装饰的统一。(2)

Product Application: C-shaped recessed lighting, beauty landscape lighting, C-shaped iron (stainless) brackets, trim between recessed walls, and different materials.






安装说明：型材需与墙体预埋工，预埋槽位，安装LED灯带，简化工序

Installation Procedure: Profiles Must Be Installed Consistently With Primary Materials, Groove Using The Adhesive. Installation Is Straightforward And Streamlined



LRD- 方形转角收口灯条 | LRD - Square Corner Trim Light Strip

型 号 (Model)	LRD10-L, LRD10-R
收口高度 (Closure Height)	10.5mm, 10.5mm
长 度 (Length)	1.00m
材 质 (Material)	铝型材 (Aluminium Alloy)
表面处理 (Surface Colour)	多种工艺, 颜色可选 (Multiple Finishes Available/Colour Options Available)
安装结构 (Corner Fitting)	安装方便, 施工简单 (Easy Installation, Simplified Procedures)



LRD- 方形转角收口灯条 | LRD - Square Corner Trim Light Strip

型 号 (Model)	LRD10, LRD10-L, LRD10-R
收口高度 (Closure Height)	10mm, 10.5mm, 10mm
长 度 (Length)	1.00m
材 质 (Material)	铝型材 (Aluminium Alloy)
表面处理 (Surface Colour)	多种工艺, 颜色可选 (Multiple Finishes Available/Colour Options Available)
安装结构 (Corner Fitting)	安装方便, 施工简单 (Easy Installation, Simplified Procedures)



产品应用: 转角收口灯条, 转角收口灯条, 转角收口灯条

Product Applications: Solid Wall Capping (For Feature Walls), Blouation differential Illuminated Capping, Half-wall Illuminated Capping



安装说明: 将收口灯条插入凹槽, 用螺丝固定, 用螺丝固定, 用螺丝固定, 用螺丝固定。

Installation Procedure: Remove & Press Card Slot Depth Of At Least 20mm On The Rear Of The Fitting Material. Secure With Screws (Screws For Brightforward Installation And Screws Used Procedures)




LUD- 内嵌硬灯条 | LUD- Embedded Rigid Led Strip

型 号 (Model)	LS212-A, LS217
嵌口宽度 (Casing Height)	12mm, 17mm
长 度 (Length)	1.05m
材 质 (Material)	铝型材 (Aluminium Alloy)
表面处理 (Surface Colour)	银白 (Silver White)
安装结构 (Casing Fitting)	免胶安装, 倒L型 (Easy Installation, Simplified Procedures)



产品应用: 墙面/地板内嵌灯条

Product Application: Flat surface Partition Light Strips For Wall and Floor Materials



安装说明: 免胶安装, 倒L型 (Easy Installation, Simplified Procedures)

Installation Procedure: Reverse Profile Dimensions, Subsequently Install Profile, Casing With Glueless Sealant, Ensuring Straightforward Installation And Streamlined Procedures




LTUD- 内嵌 (带边) 硬灯条 | LTUD- Embedded (With Flange) Rigid Light Bar

型 号 (Model)	LS212-A, LS217
嵌口宽度 (Casing Height)	12mm, 17mm
长 度 (Length)	1.05m
材 质 (Material)	铝型材 (Aluminium Alloy)
表面处理 (Surface Colour)	银白 (Silver White)
安装结构 (Casing Fitting)	免胶安装, 倒L型 (Easy Installation, Simplified Procedures)



产品应用: 墙面/地板内嵌灯条 (带边) 2mm 边距

Product Application: Flat Partition Light Strips For Wall and Floor Materials Featuring 2mm Spacing/Strips On Both Sides



安装说明: 免胶安装, 倒L型 (Easy Installation, Simplified Procedures)

Installation Procedure: Light Sources And Mounting Slot May Be Reversed For Simultaneous Or Subsequent Installation. Reverse With Glueless Sealant, The Process Offers Straightforward Installation And Streamlined Procedures

全屋精细收口/场景应用


Precision Finishing Throughout The House / Scenario applications

浴室应用

Bathroom Applications



客厅应用 | Living Room Applications



墙板收口系列 Wallboard Profile Series

规格 4 型、4 型、4 型、12 型、18 型 (标准规格)、18 型、

18 型 (加厚)、18 型 (加厚)、18 型 (加厚)、18 型 (加厚)

Comprehensive Wall Paneling System Solution Covering Joint, Joint, Joint, Joint, Joint And Joint Wall Panels For External Corners, Internal Corners,

Covering Sliding Boards, Edging And Other Functional Applications

www.lmcmetal.com



LWT09 - 墙板平面连接件 | LWT09 - Wall Panel Surface Connector

型 号 Model:	LWT09, LWT10, LWT11
位 置 Location:	板面 (墙板连接件) Beam/Wall Panel Connector
长 度 Length:	3.0m/3m
材 质 Material:	铝镁合金 (Aluminum Alloy)
表面颜色 Surface Colour:	黑色 Matte Black
安装说明 Installation Details:	见 See



产品应用：墙板之间连接件应用

Product Application: Transition Joint Finishing Between Wall Panels



安装说明：安装前与安装时请确认：1. 尺寸、2. 材质、3. 安装位置、4. 固定方式

Installation Procedure: Profiles Must Be Installed Concurrently With Primary Materials, Secured Using Nail Guns And Screws. Installation Is Straightforward, Simplifying The Process.



LWT10 - 墙板平面过渡 | LWT10 - Beam Planar Transition

型 号 Model:	LWT10, LWT11, LWT12, LWT13, LWT14
接口高度 Connect Height:	10mm, 20mm, 30mm, 40mm, 50mm
长 度 Length:	3.0m/3m
材 质 Material:	铝镁合金 (Aluminum Alloy)
表面颜色 Surface Colour:	米色、黑色 Chamfering Matte Black
安装说明 Installation Details:	见 See




产品应用：墙板之间连接件应用

Product Application: Transition Joint Finishing Between Wall Panels




安装说明：安装前与安装时请确认：1. 尺寸、2. 材质、3. 安装位置、4. 固定方式


Installation Procedure: Profiles Must Be Installed Concurrently With Primary Materials, Secured Using Nail Guns And Screws. Installation Is Straightforward, Simplifying The Process.

[illegible][illegible]

Installation/Preparation: Profiles Must Be Installed Concurrently With Primary Materials, Careful Bending & Nail Gun For Straight Forward, Streamlined Installation


[illegible][illegible]

Installation Precautions: Profiles Must Be Installed Concurrently With Primary Materials, Ground Using 6 Nail Gun For Straight Forward, Groundwood Installation




LMC - 单边收口条 | LMC - Single-sided Finishing Strip

型 号 Model	LMC04, LMC04, LMC08, LMC11, LMC18
收口高度 Closure Height	4mm, 8mm, 10mm, 12mm, 18mm
长 度 Length	3.05m
材 质 Material	铝型材 Aluminium Alloy
表面颜色 Surface Colour	灰色, 电鍍 Grey/Gold, Mirror/Bark
安装附件 Installation Details	见 See



产品应用 | 单边收口条, 单边收口

Product Application: Single-sided External Corner Finishing, Half-wall Finishing



安装附件: 铝型材收口条, 电鍍, 电鍍, 电鍍, 电鍍

Installation Procedure: Profiles Must Be Installed Consistently With Primary Materials, Covered Using A Half-Screw For Strength (Screw-inward Installation)




LWM - 铝型材收口条 | LWM - Panel External Corner Trim

型 号 Model	LWM04, LWM08
收口高度 Closure Height	4mm, 8mm
长 度 Length	3.05m
材 质 Material	铝型材 Aluminium Alloy
表面颜色 Surface Colour	灰色, 电鍍 Grey/Gold, Mirror/Bark
安装附件 Installation Details	见 See



产品应用 | 铝型材

Product Application: External Corner Trim



安装附件: 铝型材收口条, 电鍍, 电鍍, 电鍍, 电鍍

Installation Procedure: Profiles Must Be Installed Consistently With Primary Materials, Covered Using A Half-Screw For Strength (Screw-inward Installation)



LMC001 - 多用途平面连接件 | LMC001 - Multi-purpose Flat Connector

型 号 Model	LMC001
收口高度 Closure Height	6.5mm
长 度 Length	1.5m/5m
材 质 Material	铝型材 (Aluminium Alloy)
表面处理 Surface Coating	阳极 电泳 (Anodized Electrocoat)
安装规格 Installation Details	见



产品应用：多用途平面连接件

Product Application: Multi-purpose Flat Connectors



安装说明：详细请参考产品说明书。可定制颜色、表面处理、规格尺寸等。

Installation Procedure: Please refer to the product manual for details. Customization options include color, surface treatment, and specifications.



批灰收口系列 Puttying Profile Series

适用于各种墙体、吊顶等工程，可实现无缝收口，美观大方。
广泛应用于室内装饰工程，提升整体品质。

适用于各种墙体、吊顶等工程，可实现无缝收口，美观大方。


Newly Developed Surface Treatment Allows Direct Painting, Features Back-to-Back Installation, Conceals the Sealing, and Provides a Clean Finish for Straightforward Installation.

Features include Smooth Right-Angle Joints, Linear Aesthetics, Enhanced Detailing Effects.



LCEU- 悬吊 U 型工字槽 | LCEU - Plastering U-shaped Process Trough

型 号 Model	LCEU, LCEU-6, LCEU-10, LCEU-20
槽宽尺寸 Width Dimension	6mm, 10mm, 15mm, 20mm
长 度 Length	3.05m
材 质 Material	铝镁合金 Aluminium Alloy
表面处理 Surface Colour	银白色, 灰色, 电黑 Natural aluminium, Matt white, Matt Black
安装附件 Installation Details	1




产品应用：吊顶工字槽转角收口

Product Application: Concealed Channel Finish for Ceiling Corner Casing



安装图：L型工字槽转角收口示意图，铝镁合金，银白色

Installation Procedure: Prepare The Plasterboard Substrate, Remove The Profile With A Nail Gun, Adhere The Plastering Mesh, Apply The Gypsum Coat



LCEU- 悬吊铝工字槽转角收口 | LCEU - Suspended Ceiling Return (Plastering Finish)

型 号 Model	LCEU, LCEU-6, LCEU-10, LCEU-20
槽宽尺寸 Channel Width	6mm, 10mm, 15mm, 20mm
长 度 Length	3.05m
材 质 Material	铝镁合金 Aluminium Alloy
表面处理 Surface Colour	银白色, 灰色, 电黑 Natural aluminium, Matt white, Matt Black
安装附件 Installation Details	1



产品应用：吊顶工字槽转角收口

Product Application: Concealed Channel Finish for Ceiling Corner Casing



安装图：L型工字槽转角收口示意图，铝镁合金，银白色

Installation Procedure: Prepare The Plasterboard Substrate, Remove The Profile With A Nail Gun, Adhere The Plastering Mesh, Apply The Gypsum Coat



LCCM04

LCCM04-窄边阳角收口 | LCCM04 - Narrow-edge Internal Corner Trim

型 号 / Model	LCCM04
饰面/材质 / Item, 表面/表面处理 / Plaster Thickness	Item: The Surface is Suitable For Painting/With Emulsion/Paint
长 度 / Length	1.00m
材 质 / Material	铝型材 / Aluminium Alloy
表面/饰面 / Surface Colour	银灰色 / 可定制颜色 / Natural aluminium finish (Ready For Painting)
安装/附件 / Installation Details	见 /



产品应用：铝型材窄边阳角收口

Product Application: Aluminium Alloy Narrow-edge Plastering Corner Trim



安装说明：在准备好石膏板后，将型材安装在石膏板上，然后将石膏板表面涂上腻子，即可安装。

Installation Procedure: Once The Plasterboard is Prepared, Insert The Profile Using A Nail Gun. After The Plasterboard is Ready, Apply A Coat Of Filler And The Profile Surface May Be Painted Directly.



LCCM04-0



LCCM04-0



LCCM04-0


LCCM-上墙 L 型阳角收口/收口 | LCCM - Upward Return L-shaped System Board/Corner Trim coating and finishing

型 号 / Model	LCCM04-0, LCCM04-0, LCCM04-0
饰面/材质 / Item, 表面/表面处理 / Plaster Thickness	Item: The Surface is Suitable For Painting/With Emulsion/Paint
长 度 / Length	1.00m
材 质 / Material	铝型材 / Aluminium Alloy
表面/饰面 / Surface Colour	银灰色 / 可定制颜色 / 电铸 / Natural aluminium (Ready For Painting) Matt Black
安装/附件 / Installation Details	见 /



产品应用：上墙 L 型阳角收口/收口，铝型材与石膏板/石膏板/石膏板

Product Application: Finishing L-shaped Plasterboard with Plaster Transition into Between Painted Walls and Different Materials



安装说明：在准备好石膏板后，将型材安装在石膏板上，然后将石膏板表面涂上腻子，即可安装。

Installation Procedure: The Profile Must Be Pre-embedded In The Junction With Plasterboard, Fill With Specialized Joint Compound And After Plastering Made.

[illegible]


Student Identification: Student ID, School Enrollment Status, GPA, Degree, Gender, Age, Address, School Name, and Address



Installation Procedure: The Profile Mount Kit Pre-constructed in The Location With Plywood, Fit With Specialist Join Compound and With Plywood Back.

[illegible]

© 2004 Blackwell Publishing Ltd *Journal of Internal Medicine* 255: 103–110



Installation/Preparation: Score The Waterboard Substrate Is Prepared.
Remove The Profile Using A Hall Saw, With The Planing Blade.
Apply A Coat Of Filler And The Profile Surface Can Be Painted
Directly.



LC807

LC807- 抓角角批方收口 | LC807 - Grabapple Corner Plastering And Finishing

型 号 Model	LC807
规格厚度 Size, 厚度 Thickness Size	The Surface is Suitable for Plastering with Emulsion Paint
长 度 Length	1.00m
材 质 Material	铝合金 Aluminium Alloy
表面处理 Surface Colour	银白色 可喷涂油漆 Natural Aluminium (Ready For Painting)
安装附件 Installation Details	/



产品应用 | 抓角批角收口

Product Application Grabapple Corner Filler For Finishing Edges



安装步骤：1. 准备批角基层，2. 用气钉枪固定收口，3. 批角腻子，4. 批角腻子

Installation Procedure: Prepare The Plasterboard Substrate, 1. Prepare The Plasterboard Substrate, 2. Secure The Profile Using A Nail Gun, 3. Apply The Plastering Mesh, 4. Apply The Plastering Mesh, 5. Apply The Plastering Mesh



LC808D00


LC808D00- 悬浮吊顶发光收口 | LC808D00 - Suspended Ceiling Illuminated Trim

型 号 Model	LC808D00
规格厚度 Size, 厚度 Thickness Size	The Surface is Suitable for Plastering with Emulsion Paint
长 度 Length	1.00m
材 质 Material	铝合金 Aluminium Alloy
表面处理 Surface Colour	银白色 可喷涂油漆 银白色 Natural Aluminium (Ready For Painting, Silver Black)
安装附件 Installation Details	/



产品应用 | 悬浮吊顶发光收口

Product Application Suspended Ceiling Illuminated Trim



安装步骤：1. 准备批角基层，2. 用气钉枪固定收口，3. 批角腻子，4. 批角腻子

Installation Procedure: Prepare The Plasterboard Substrate, Secure The Profile Using A Nail Gun, Apply The Plastering Mesh, Apply The Plastering Mesh




AC100 - 3/4" x 3/4" x 1/2" | AC100 - Primer-coated Luminous Corner Trim

名	名 Material	ACRON 2, GARDOL®
使用用途 Uses , (使用可能用途) Uses Business Uses The Surface is Suitable for Painting with Emulsion Paint		
性 性 Properties		45 minutes
材 材 Material	材料名 Material	材料名 Material
使用用途 Surface Colour	使用色 (可能用途) Material	Material
使用用途 Materialisation Results		2



Table 1

[illegible]

1. *Journal of the American Medical Association*, 2000; 284: 2689-2695.

1. 1990-1991	2. 1991-1992
--------------	--------------

Installation Process Prepares The System Board Substrate.
Secure The Profiles With A Nail Gun. Apply Joint Compound
Then Apply A Coat Of Putty. The Profiles Surface Can Be Painted
Directly.




LCCS - 800-967-9000 | LCCS - Greater Cleveland Main Coast Firefighting

型 号 (Model)	LS100
英文名称 (Name, 请同时标注汉语拼音) (Name in English and Pinyin)	Simulation Point
材 质 (Material)	铝型材 (Aluminum)
材 质 (Material)	铝型材 (Aluminum Alloy)
表面处理 (Surface Color)	银粉 (银粉漆) (Silver Powder (Silver Powder))
安装说明 (Installation Details)	1

[illegible]

Keywords: child sexual abuse; disclosure; social support

[illegible]

1. <i>Staphylococcus aureus</i>	2. <i>Staphylococcus aureus</i>
---------------------------------	---------------------------------

Installation Process: Prepare The Substrate, Seal Substrate, Secure The Profile With A Nail Gun, Apply Joint Compound (Which Apply A Layer Of Joint Compound, The Profile Surface Can Be Polished Directly)

[illegible]

Frontiers | <https://doi.org/10.3389/fpsyg.2022.881111> | www.frontiersin.org | <https://www.frontiersin.org/journal/10.3389/fpsyg.2022.881111>




Installation Process: Prepare The Signage Board Substrate
 Remove The Profiles With A Nail-Bar. Apply Joint Compound
 Mastic. Apply A Layer Of Joint Compound. The Profile Surface
 Can Be Reused Elsewhere.



呼 号 (Callsign):	GSX1.3
船主/船務 (Owner/Operator):	U.S. Navy
呼 號 (Callsign):	440000
船 名 (Name):	羅斯福 (Roosevelt)
船體顏色 (Hull Colour):	銀白色 (可變為藍色) / 電鍍 Natural Aluminium (Polishing), Silver Black
介紹/說明 (Introduction/Details):	?



Product Identification: Company Name/Contact Name, Phone/Fax Email, Web Site/URL, Street Address, City, State, Zip



Installation Procedure: Profile Must Be Pre-embedded Into Wall
 Adhesive Must Be Filled With Specialized Joint Compound
 And Reinforced With Mesh Tape



PDFL0010、上盖 T 型材带固定螺钉及密封胶 (PDFL0010 - Upper Section T-shaped Single-layer Aluminum Board With Screws, Sealing and Finishing)

型 号 / Model	PDFL0010, PDFL0015, PDFL0020
适用基材 / 适用层 / Suitable For With	Aluminum Alloy Board / Natural Surface Can Be Polished With Latex Paint
长 度 / Length	3.05m
材 质 / Material	铝合金 / Aluminium Alloy
表面颜色 / Surface Colour	银白色 (可喷涂色漆)、阳极 / Natural aluminium (Painting), Anodic Black
安装附件 / Installation Details	1



产品图 | 上盖 T 型材带固定螺钉及密封胶 (产品图与安装附件图仅供参考)

Product appearance drawing | T-shaped single-layer aluminum board with finishing, transition and finishing between front plate and different material



安装说明：型材需带胶，与铝基板及密封胶需同时安装在型材的固定孔位置

Installation Procedure: Profile Must Be Pre-embedded Joint With Aluminum Board Must Be Filled With Specialized Joint Compound And Sealed With Black Tape




PDFL0010、上盖 T 型材带固定螺钉及密封胶 (PDFL0010 - Upper Section T-shaped Single-layer Aluminum Board With Screws, Sealing and Finishing)

型 号 / Model	PDFL0010, PDFL0015, PDFL0020
适用基材 / 适用层 / Suitable For With	Aluminum Alloy Board / Natural Surface Can Be Polished With Latex Paint
长 度 / Length	3.05m
材 质 / Material	铝合金 / Aluminium Alloy
表面颜色 / Surface Colour	银白色 (可喷涂色漆)、阳极 / Natural aluminium (Painting), Anodic Black
安装附件 / Installation Details	1



产品图 | 上盖 T 型材带固定螺钉及密封胶 (产品图与安装附件图仅供参考)

Product appearance drawing | T-shaped single-layer aluminum board with finishing, transition and finishing between front plate and different material



安装说明：型材需带胶，与铝基板及密封胶需同时安装在型材的固定孔位置

Installation Procedure: Profile Must Be Pre-embedded Joint With Aluminum Board Must Be Filled With Specialized Joint Compound And Sealed With Black Tape



L200A10-6

铝型材 L200A10-6 (L200A10-6) (L200A10-6) - Upper Surface 5-Shape Inside Super Squeeze Board Side Covering and Fixing

型 号 Model L200A10-6

适用尺寸 (适用) 适用尺寸 (适用) Suitable For 10mm Squeeze Board / Natural Surface Can Be Reinforced With Latex Tape

长 度 Length 1.00m

材 质 Material 铝型材 (Aluminium Alloy)


表面处理 Surface Colour 银灰色 (可喷涂黑色) / 阳极 (Natural Aluminium (Paintable) Matte Black)

安装说明 Installation Details 1



产品应用 上层 = 5-Shape Inside Super Squeeze Board / 自然表面可喷涂黑色 / 阳极

Product Application Fixing in 5-Shape Inside Super Squeeze Board, Natural Surface Can Be Reinforced With Latex Tape



安装说明 1. 将铝型材 L200A10-6 放入 10mm Squeeze Board 上方。2. 将铝型材 L200A10-6 放入 10mm Squeeze Board 上方。3. 将铝型材 L200A10-6 放入 10mm Squeeze Board 上方。4. 将铝型材 L200A10-6 放入 10mm Squeeze Board 上方。

Installation Procedure Profile Must Be Pre-embedded Joint With Squeeze Board Must Be Filled With Specialized Joint Compound And Reinforced With Latex Tape



L200C06

铝型材 L200C06 (L200C06) (L200C06) - Double Super Squeeze Board Suspended Ceiling With Squeeze Ceiling Light / Natural With Reinforcing and Edge Fixing

型 号 Model L200C06

适用尺寸 (适用) 适用尺寸 (适用) Suitable For 6 Squeeze Board / Width 10mm, Flange Thickness 6mm

长 度 Length 1.00m

材 质 Material 铝型材 (Aluminium Alloy)



表面处理 Surface Colour 银灰色 (可喷涂黑色) / 阳极 (Natural Aluminium (Paintable) Matte Black)

安装说明 Installation Details 1



产品应用 上层 = 6-Shape Inside Super Squeeze Board / 自然表面可喷涂黑色 / 阳极

Product Application Fixing in 6-Shape Inside Super Squeeze Board, Natural Surface Can Be Reinforced With Latex Tape



安装说明 1. 将铝型材 L200C06 放入 6mm Squeeze Board 上方。2. 将铝型材 L200C06 放入 6mm Squeeze Board 上方。3. 将铝型材 L200C06 放入 6mm Squeeze Board 上方。4. 将铝型材 L200C06 放入 6mm Squeeze Board 上方。

Installation Procedure Profile Must Be Pre-embedded Joint With Squeeze Board Must Be Filled With Specialized Joint Compound And Reinforced With Latex Tape




PL-711 - 美國海軍部法案 | PL-511 - Congress Board-Oversight Control Act

P00013 - 478-50769012 | P00013 - Decoupler Board Inside Corner View

Close-up of a black and silver metal track with a sliding component.



Installation Procedures: Profile Mount Re-Represented, Inter-
With Alignment Board Connect the First With Operational Joint
Connect the Joint Re-Represented With Mount Type



Installation Process Profiles Must Be Pre-Installed, Joint With Spline Board Should Be Filled With Specialized Joint Compound And Reinforced With Joint Mesh. Profile Surfaces Can Be Painted Directly.




PSL004 - 石膏板收口工艺 | PSL004 - Gypsum Board Finishing Process

型 号 Model:	PSL004
收口高度 Closure Height:	12mm
长 度 Length:	3.05m
材 质 Material:	铝镁合金 Aluminium Alloy
表面颜色 Surface Colour:	银灰色 (可定制颜色) , 阳极 Natural Aluminium (Paintable), Matte Black
安装说明 Installation Details:	见 See




产品特点: 适用于石膏板收口工艺, 铝镁合金材质。
Product Application: Suitable for ceiling and corner finishing between gypsum board and surface with hollow structure. Compatible with most hollow wall types.



安装说明: 石膏板收口, 与石膏板交接处, 需用密封胶填充并加固。
Installation Procedure: Profile must be pre-embedded into joint. With Gypsum Board must be filled with Specialized Joint Compound and Reinforced with Mesh Tape.

安装说明: 石膏板收口, 与石膏板交接处, 需用密封胶填充并加固。
Installation Procedure: Profile must be pre-embedded into joint. With Gypsum Board must be filled with Specialized Joint Compound and Reinforced with Mesh Tape.



PSL004 - 石膏板收口工艺 | PSL004 - Gypsum Board Finishing Process

型 号 Model:	PSL004, PSL005, PSL006, PSL007, PSL008
收口高度 Closure Height:	12mm (适用于石膏板) / suitable for Gypsum Board up to 12mm Thick, with a Panel Thickness of 12mm
长 度 Length:	3.05m
材 质 Material:	铝镁合金 Aluminium Alloy
表面颜色 Surface Colour:	银灰色 (可定制颜色) , 阳极 Natural Aluminium (Paintable), Matte Black
安装说明 Installation Details:	见 See



产品特点: 适用于石膏板收口工艺, 铝镁合金材质。
Product Application: Suitable for ceiling and corner finishing between gypsum board and surface with hollow structure. Compatible with most hollow wall types.



安装说明: 石膏板收口, 与石膏板交接处, 需用密封胶填充并加固。
Installation Procedure: Profile must be pre-embedded into joint. With Gypsum Board must be filled with Specialized Joint Compound and Reinforced with Mesh Tape.

安装说明: 石膏板收口, 与石膏板交接处, 需用密封胶填充并加固。
Installation Procedure: Profile must be pre-embedded into joint. With Gypsum Board must be filled with Specialized Joint Compound and Reinforced with Mesh Tape.




PC12 - 铝加铝角收口 | PC12 - Corner Joint Finishing

型 号 / Model:	PC12
适用厚度 / Suitable Thickness:	适用厚度 4mm (suitable for Gypsum boards up to 4mm Thick, With a Plaster Thickness of 2.5mm)
长 度 / Length:	3.05m
材 质 / Material:	铝加铝 / Aluminium Alloy
表面处理 / Surface Colour:	银白色 (可喷涂颜色) / Natural Aluminium Finish (Ready for Painting)
安装说明 / Installation Details:	见 / See



产品特点: 铝加铝角收口, 铝加铝角收口
Product Application: Corner Finishing For Receiving Natural Surface Suitable for later Paint Application



安装说明: 铝加铝角收口, 铝加铝角收口, 铝加铝角收口, 铝加铝角收口, 铝加铝角收口, 铝加铝角收口, 铝加铝角收口, 铝加铝角收口, 铝加铝角收口, 铝加铝角收口
Installation Process: Profiles Must Be Pre-embedded. Joints With Gypsum Board Should Be Filled With Specialized Joint Compound And Reinforced With Joint Mesh. Profile Surfaces Can Be Painted Directly




PC40 - 铝加铝二角用角收口 | PC40 - Gypsum Board Secondary Ceiling Trim

型 号 / Model:	PC40
适用厚度 / Suitable Thickness:	适用厚度 4mm (suitable for Gypsum boards up to 4mm Thick, With a Plaster Thickness of 2.5mm)
长 度 / Length:	3.05m
材 质 / Material:	铝加铝 / Aluminium Alloy
表面处理 / Surface Colour:	银白色 (可喷涂颜色) / Natural Aluminium Finish (Ready for Painting)
安装说明 / Installation Details:	见 / See



产品特点: 铝加铝二角用角收口, 铝加铝二角用角收口
Product Application: Secondary Ceiling Trimming For Gypsum Board Natural Surface Suitable for later Paint Application



安装说明: 铝加铝二角用角收口, 铝加铝二角用角收口, 铝加铝二角用角收口, 铝加铝二角用角收口, 铝加铝二角用角收口, 铝加铝二角用角收口, 铝加铝二角用角收口, 铝加铝二角用角收口, 铝加铝二角用角收口, 铝加铝二角用角收口
Installation Process: Profiles Must Be Pre-embedded. Joints With Gypsum Board Should Be Filled With Specialized Joint Compound And Reinforced With Joint Mesh. Profile Surfaces Can Be Painted Directly




PR12- 铝角线收边收口 | PR12 - Corner Finishing for Plastering

型 号 Model:	PR12
适用厚度 (适用厚度) Suitable for Thickness (适用厚度):	Up to 10mm (10mm) (suitable for Gypsum boards up to 10mm Thick, with a Plaster Thickness of 2.5mm)
长 度 Length:	3.05m
材 质 Material:	铝镁合金 (Aluminium Alloy)
表面处理 Surface Colour:	银灰色 (可喷涂油漆) Natural Aluminium Finish (Ready for Painting)
安装说明 Installation Details:	见说明 See Manual



产品特点：铝角线收边，铝角线收边收口，铝角线收边收口，铝角线收边收口。
Product Application: Corner Joint Finishing for Plastering. Suitable for gypsum boards up to 10mm thick. with compound thickness.
注意：表面处理为阳极氧化，可喷涂油漆。



产品特点：铝角线收边，铝角线收边收口，铝角线收边收口，铝角线收边收口。
Product Application: Corner Joint Finishing for Plastering. Suitable for gypsum boards up to 10mm thick. with compound thickness.
注意：表面处理为阳极氧化，可喷涂油漆。

Installation Procedure: Profile Must Be Pre-embedded. Joint With Gypsum Board Should Be Filled With Specialized Joint Compound and Reinforced With Joint Mesh. Profile Surface Can Be Finished Directly.




PRK- 铝角线收边收口 | PRK- Gypsum Board Curved Corner Board

型 号 Model:	PRK10, PRK15, PRK20
适用厚度 (适用厚度) Suitable for Thickness (适用厚度):	10mm, 15mm, 20mm
长 度 Length:	3.05m
材 质 Material:	铝镁合金 (Aluminium Alloy)
表面处理 Surface Colour:	银灰色 (可喷涂油漆) Natural Aluminium Finish (Ready for Painting)
安装说明 Installation Details:	见说明 See Manual



产品特点：铝角线收边，铝角线收边收口，铝角线收边收口，铝角线收边收口。
Product Application: Gypsum Board Curved Corner Board. May Be Used for Corner Application Where Gypsum Board Thickness Differs from Plaster.




产品特点：铝角线收边，铝角线收边收口，铝角线收边收口，铝角线收边收口。
Product Application: Gypsum Board Curved Corner Board. May Be Used for Corner Application Where Gypsum Board Thickness Differs from Plaster.

Installation Procedure: Profile Must Be Pre-embedded. Joint With Gypsum Board Should Be Filled With Specialized Joint Compound and Reinforced With Joint Mesh. Profile Surface Can Be Finished Directly.




PRS- 行角板直角的角条 | PRS- Gypsum Board Right-Angle Corner Bead

型 号 Model:	PRS-01
显 示 图 Display draw:	15.5mm
长 度 Length:	3.000m
材 质 Material:	铝镁合金 Aluminium Alloy
表面处理 Surface Colour:	银灰色 (可任意喷涂) Natural Aluminium Finish (Ready For Painting)
安装说明 Installation Details:	见



产品图 | 行角板直角的角条, 用于石膏板与石膏板之间的角条。

Product Application: Gypsum Board Right-Angle Corner Bead Used for Gypsum Board Corner Applications With Different Materials.



安装说明 | 行角板直角的角条, 用于石膏板与石膏板之间的角条。安装时, 应先将角条安装在角条上, 然后用石膏板固定角条。

Installation Process: Profiles Must Be Pre-embedded Joints With Gypsum Board Should Be Filled With Specialized Joint Compound And Reinforced With Joint Mesh. Profile Surfaces Can Be Painted Directly.




PRS-2 行角板直角的角条 | PRS-2 Gypsum Board Right-Angle Corner Bead

型 号 Model:	PRS-02
显 示 图 Display draw:	(20mm 厚石膏板用) suitable for Gypsum Boards up to 20mm Thick, With a Flange Thickness of 4mm
长 度 Length:	3.000m
材 质 Material:	铝镁合金 Aluminium Alloy
表面处理 Surface Colour:	银灰色 (可任意喷涂) Natural Aluminium Finish (Ready For Painting)
安装说明 Installation Details:	见



产品图 | 行角板直角的角条, 用于石膏板与石膏板之间的角条。

Product Application: The Bead Is Used For The Fixing of a Vertical With a Joint Mesh and Stop. The Reinforced Surface is Compatible With a Joint Mesh Application.



安装说明 | 行角板直角的角条, 用于石膏板与石膏板之间的角条。安装时, 应先将角条安装在角条上, 然后用石膏板固定角条。


Installation Process: Profiles Must Be Pre-embedded Joints With Gypsum Board Should Be Filled With Specialized Joint Compound And Reinforced With Joint Mesh. Profile Surfaces Can Be Painted Directly.



PCB04 - 4000 - 9000 Series | PCB04 - Gypsum Board Secondary Ceiling Tiles

[illegible]

Photo Application Tuesday Ending Sept. 10th 10:00am-12:00pm, First Respond
Must Be Accompanied With Adult. Please Call 603-882-1111



Installation Process Profiles Make the Process Simpler. Joining With Systems Based Around the Pipe With Specialized Join Components and Reinforced With Reinforced Profile Surfaces Can Be Achieved Simply.




P4 - 斜邊二端單邊固定 / P4 - Beveled Edge Trim For A Two-sided Sloped Ceiling

图 号 (Index)	图例
图 名 (Graphic name)	图例
图 号 (Image)	图例
图 名 (Material)	图例
图 名 (Surface Color)	图例 (可再喷涂) Natural Aluminum Finish (Ready For Painting)
图 名 (Installation Details)	图例



Product Application: Resinoid Varnishing; Soling Sizing with Resin Sizing; Resin Sizing of Wood/Plastic; Resinoid Sizing of Wood/Plastic



Installation: Pressure Profiles Must Be Perpendicular Joins With
Sprocket Board Should Be Filled With Specialized Joint Compound
Joint and Reinforced With Joint Mesh. Profile Surface Can Be
Painted Concrete

全屋精细收口/场景应用


Precision Finishing Throughout The Home / Scenarios applications

客厅应用

Living Room Application



餐厅应用 | Restaurant App



黄铜收口系列

Brass Tile Trim Series

适用于各种场景，适用于各种材质的过渡和收口，包括地板、墙面、

橱柜之间的过渡和收口等场景应用。黄铜、铜、铝、不锈钢。

Functions include Covering Transitions Between Wood/Flooring, Decorative Transitions Between Tiles And Stone, Edge Trimming, And Finishing Transitions Between Different Materials. Authentic Materials, Precise Craftsmanship, And High Quality

www.lmcmetal.com



型 号 (Model):	BF6212, BF6218, BF6219
测量尺寸 (Measurement):	12mm, 18mm, 19mm
型 号 (Range):	100µm
材 质 (Material):	碳纤维 (Carbonium fiber)
使用温度 (Working Temper):	环境 + 100℃ (Room Natural Broadest Temp)
使用限制 (Installation Restrict):	-

[illegible]

Product Classification: General Household Item - Household Cleaning






7070 角 - 平面过渡条 / 分隔装饰条 | 7070 Corner - Flat Transition Strip / Decorative Divider Strip

型 号 (Model)	7070 Corner
规格尺寸 (Footage/Width)	3000mm
长 度 (Length)	1000mm
材 质 (Material)	铝 (Al) / Brass
表面处理 (Surface Colour)	自然拉丝 (Natural Brushed Finish)
安装说明 (Installation Details)	见 (See)



产品应用：平面过渡条 / 分隔装饰条

Product Application: Curved Transition Strip / Decorative Divider Strip



安装说明：规格尺寸：3000mm x 1000mm，自然拉丝，见 (See) 安装说明，见 (See) 安装说明

Installation Process: Pre-cut Dimensions, Retrofit Installation Of Profile, Nail from Adhesive Fixation, Easy Installation, Remove: Used Procedures




7070 角 - 直角保护条 | 7070 Corner - Brass Corner Guard Strip

型 号 (Model)	7070 Corner
规格尺寸 (Footage/Width)	3000mm
长 度 (Length)	1000mm
材 质 (Material)	铝 (Al) / Brass
表面处理 (Surface Colour)	自然拉丝 (Natural Brushed Finish)
安装说明 (Installation Details)	见 (See)



产品应用：直角保护条 / 分隔装饰条

Product Application: Corner Protection and Striping for Materials Such as Ceramic / Standard Wood/Branding



安装说明：规格尺寸：3000mm x 1000mm，自然拉丝，见 (See) 安装说明，见 (See) 安装说明

Installation Process: Pre-cut Dimensions, Retrofit Installation Of Profile, Nail from Adhesive Fixation, Easy Installation, Remove: Used Procedures




BMT- 小角饰边条 | BMT- Small Corner Trim Strip

型 号 (Model)	BMT-1, BMT-2
饰边尺寸 (Framing Width)	12mm, 12.7mm
长 度 (Length)	2.1m/6.9ft
材 质 (Material)	黄铜 (Brass)
饰面颜色 (Surface Colour)	黄铜自然拉丝 (Brass Natural Brushed Finish)
安装说明 (Installation Details)	见



产品应用 | 应用范围 | Application

Product Application: Inside Corner Finishing, Countertop and Sill Edge Finishing



安装说明：按材料尺寸精确施工，确保贴合度，安装便捷，施工迅速。

Installation Process: Profile installation must be performed concurrently with primary material installation. Covered with tile adhesive, it offers convenient installation and streamlined procedures.




BMT- 角饰边条、地板分界线 | BMT- Corner Trim, Floor Divider Strip

型 号 (Model)	BMT-1, BMT-2
饰边尺寸 (Framing Width)	12.7mm, 25mm
长 度 (Length)	2.1m/6.9ft
材 质 (Material)	黄铜 (Brass)
饰面颜色 (Surface Colour)	黄铜自然拉丝 (Brass Natural Brushed Finish)
安装说明 (Installation Details)	见



产品应用 | 应用范围 | Application

Product Application: Inside Corner Finishing, Countertop and Sill Edge Finishing, Floor Divider Strip



安装说明：按材料尺寸精确施工，确保贴合度，安装便捷，施工迅速。

Installation Process: Profile installation must be performed concurrently with primary material installation. Covered with tile adhesive, it offers convenient installation and streamlined procedures.




BTL- 阳角 L 形收口线 | BTL - Corner L-Shaped Trim

型 号 (Model)	BTL, BTL, BTL, BTL
凸口高度 (Convex Height)	10mm, 12mm, 12mm, 15mm
长 度 (Length)	2.19m
材 质 (Material)	铝 (Al)
表面颜色 (Surface Colour)	自然拉丝铝 (Natural Brushed Finish)
安装说明 (Installation Details)	见 (See)



产品应用：阳角收口，墙角线收口，墙角线收口，墙角线收口，墙角线收口

Product Applications: Inside Corner Finishing, Single side Finishing For Inside Walls, Level Transition Finishing, Half wall Finishing, Countertop and Sill Finishing



产品应用：阳角收口，墙角线收口，墙角线收口，墙角线收口，墙角线收口

Installation Process: Profile installation, Material removal, Material removal, Material removal, Material removal





BTPS-10 - 平面过渡线 | BTPS-10 - Planar Transition Line

型 号 (Model)	BTPS-10
凸口高度 (Convex Height)	10mm
长 度 (Length)	2.19m
材 质 (Material)	铝 (Al)
表面颜色 (Surface Colour)	自然拉丝铝 (Natural Brushed Finish)
安装说明 (Installation Details)	见 (See)



产品应用：阳角收口，墙角线收口，墙角线收口，墙角线收口，墙角线收口



产品应用：阳角收口，墙角线收口，墙角线收口，墙角线收口，墙角线收口

Installation Process: Profile installation, Material removal, Material removal, Material removal, Material removal




800-855-6869 | 800-855-6869

[illegible]

© 2005 Blackwell Publishing Ltd, *Journal of Internal Medicine* 257: 105–112

Product Application: *Corrosion Inhibitors Between Different Material Surfaces Such as: Tile, Stone, Wood Flooring, and Steel Surfaces*



[Home](#)
[About Us](#)
[Contact Us](#)
[Privacy Policy](#)
[Terms of Service](#)

Installation Process: Install After Recording Dimensions For The
Hole, Secure With Glue, Sealant / Fasteners Convenient Installa-
tion And Versatility / Procedures.



NU-U 型平流式沉砂池 | NU-U Type Fluvial Transition Line

型 号 / Model:	BK-8, BK-10, BK-FI, BK-D9
规格尺寸 / Appearance Pattern:	6mm, 8mm, 10mm, 20mm
材 质 / Sample:	24 Photos
材 质 / Material:	美国 / Brazil
表面处理 / Surface Coating:	美国冰晶石 http://www.brazilnaturalbreast.com
安装附件 / Installation Details:	7'



1990	1991	1992	1993
1994	1995	1996	1997

Product Applications: Resin
Transitions Between Different
Material Environments Such As To
Glass, Wood, Housing, And Other
Plastics

[illegible][illegible]



BTP- 丁字平面的过渡条 | BTP - T-shaped Flat Transition Strip

型 号 (Model)	BT100, BT15, BT100-L, BT1-L, BT1-S, BT100-S
规格尺寸 (Footage Width)	10mm, 15mm, 100mm, 120mm, 15mm, 20mm
长 度 (Length)	1.2m/1m
材 质 (Material)	黄铜 (Brass)
表面颜色 (Surface Colour)	黄铜本色/拉丝 (Brass Natural/Brushed Finish)
安装详情 (Installation Details)	1



产品应用：实木、石材、瓷砖、玻璃、金属、塑料、木材等。
Product Application: Realwood, Transition between Different Materials such as the Stone, Wood, Ceramic, Metal, Marble, and other surfaces to make seamless.



安装方便：可现场施工，也可以预装。10mm，15mm规格条，安装简单，施工快。

Installation Process: Can be installed on-site with Gun, or pre-assembled for later. 10mm/15mm Length, Easy Installation with Simple Tools.




BLP- 直角收边线 | BLP - Right-angle Edge Trim

型 号 (Model)	BLP101, BLP100, BLP101-S
接口高度 (Groove Height)	15mm, 20mm
长 度 (Length)	2.1m/1m
材 质 (Material)	黄铜 (Brass)
表面颜色 (Surface Colour)	黄铜本色/拉丝 (Brass Natural/Brushed Finish)
安装详情 (Installation Details)	1



产品应用：实木、石材、瓷砖、玻璃、金属、塑料、木材等。
Product Applications: Realwood, Right-angle joints, Natural Corner Trim, Countertop and Sink Threshold Trim.




产品应用：实木、石材、瓷砖、玻璃、金属、塑料、木材等。
Installation Process: Can be installed on-site with Gun, or pre-assembled for later. 10mm/15mm Length, Easy Installation with Simple Tools.



BT12.5

BT - 平面过渡线 (木地板) | BT - Flat Transition Strip (Wood Flooring)

型 号 (Model)	BT12.5
接口高度 (Closure Height)	12.5mm
长 度 (Length)	27mm
材 质 (Material)	黄铜 (Brass)
表面颜色 (Surface Colour)	黄铜本色/拉丝 (Brass Natural/Brushed Finish)
安装详情 (Installation Details)	2



产品应用: 木地板、石材、瓷砖等
不同材料之间的过渡

Product application: Seamless
Transitions Between Different
Materials Such As Wood Flooring
And Tiles

安装步骤: 1. 测量尺寸
2. 切割金属条
3. 安装固定

安装步骤: 1. 测量尺寸
2. 切割金属条
3. 安装固定



BT12.5


BT - 平面过渡线 (木地板) | BT - Flat Transition Strip (Wood Flooring)

型 号 (Model)	BT12.5
接口高度 (Closure Height)	12.5mm
长 度 (Length)	27mm
材 质 (Material)	黄铜 (Brass)
表面颜色 (Surface Colour)	黄铜本色/拉丝 (Brass Natural/Brushed Finish)
安装详情 (Installation Details)	2



产品应用: 木地板、石材、瓷砖等
不同材料之间的过渡

Product application: Seamless
Transitions Between Different Materials Such As Wood
Flooring, Stone, And Wood Flooring, As Well As
Transitions Between Different Materials



安装步骤: 1. 测量尺寸
2. 切割金属条
3. 安装固定

安装步骤: 1. 测量尺寸
2. 切割金属条
3. 安装固定





HTC - 華碩 C 型雙面開口鏡 | HTC - Single-sided C-shaped Mirror View only

[illegible]

Year	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099
1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	

Product Application: Used for testing the transition between different materials such as stone, and aluminium, as well as stone to stone transitions and stone to metal joints.




参考文献: [1] 王德明, 王德明. 中国城市人口空间均衡与区域可持续发展. 北京: 中国人口出版社, 2004.

Installation Process: Profile Installation Must Be Performed Correctly. With Main Material/Installation. Remove With Silicone Sealant. Installation Is: Reinforcement And Strengthening




Figure 1: Schematic diagram of the experimental setup. A subject is seated at a table, viewing a video screen. A video camera is positioned above the screen. A horizontal bar is placed on the table, with a vertical rod attached to it. The rod is connected to a motor unit. The motor unit is connected to a power source. The video screen displays the visual feedback of the hand position.

型 号 (Model)	MT20A, MT21A, MT22A, MT24A, MT25A, MT26A
接口语言 (Connect language)	Chinese, German, Japanese, Korean, Russian, Spanish
材 质 (Material)	2318 铝
材 质 (Material)	美国 6061 铝
制造标准 (Manufacture Standard)	美国军用标准 (MIL-STD-883C Method A)
中国标准 (China Standard)	GB



Year	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099
1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	

Abstract Background: Health Monitoring 2 or 3 (HMH2 or 3) is the second (third) follow-up visit for the Home-Based Blood Pressure and Other Surveys (HBBS) Study. **Methods:**

[illegible]

Installation Process: Profile Installation/With Thermal Camera
ready/With Main Structural Construction. Access/With Climate
System For Connected Installation And Structural Protection




CR- 铝角包角收边线 | CR- Curved Corner Trim

型 号 Model	CR15, CR25
包角高度 Closure Height	15mm, 25mm
长 度 Length	2.000m
材 质 Material	不锈钢 SS304
表面颜色 Surface Colour	多种工艺, 多种颜色 Multiple Finishes and Colors Available
安装图 Installation Details	1



产 品 用 途： 铝角包角、铝角包边、铝
包边包角、铝包边包角

Product Applications: Internal
Corner Finishing, Internal Corner
Finishing, Countertop and Step
Finishing, Local Transition Finish-
ing.



产 品 用 途： 铝
角包角、铝角包边、
铝包边包角、铝包边包角

Installation Process: Profile
Installation Must Be
Performed
Consequently With Primary
Material Work, which Involves
With The Adhesive And The
Mounting Screws And
Mounting Screws.




SUST- 不锈钢实心 T 条 | SUST- Stainless Steel Solid T-Bar

型 号 Model	SUST15, SUST25, SUST35, SUST45, SUST55, SUST65
厚度尺寸 Thickness Width	15mm, 25mm, 35mm, 45mm, 55mm, 65mm
长 度 Length	2.000m
材 质 Material	不锈钢 SS304
表面颜色 Surface Colour	多种工艺, 多种颜色 Multiple Finishes and Colors Available
安装图 Installation Details	1



墙 角、地 角、窗 口 等 处 的 平 面 包 边 收 边 工 程

Flat Transition joints for Wall Panels, Flooring, Tiles, Glass, and Other Materials



安 装 过 程： 按 照 图 纸 中 的 尺 寸 进 行 安 装， 确 保 安 装 质 量， 确 保 工 程

Installation Process: Install After Measuring Dimensions for Flat
Bars, Ensure With Glueless Sealant. Features Convenient Installation
and Simplified Procedures.



SFR-100


SFR- 高低差收口条 | SFR - Height Differential Trim Strip

型 号 (Model)	CFR-100
收口高度 (Closure Height)	12.5mm
长 度 (Length)	3.000m
材 质 (Material)	不锈钢 (SS304)
表面处理 (Surface Colour)	多种工艺, 多种颜色 (Multiple Finishes And Colors Available)
安装附件 (Installation Details)	1



产品应用: 内外角收口, 高低差收口, 玻璃幕墙收口, 幕墙收口

Product Application: Internal Corner Finishing, Internal Corner Finishing, Glass Curtain Wall Finishing, Glass Curtain Wall Finishing



安装流程: 1. 将SFR-100插入角部, 2. 将SFR-100插入角部, 3. 将SFR-100插入角部, 4. 将SFR-100插入角部

Installation Process: Profile Installation Must Be Performed Concurrently With Primary Material Installation. Secured With Tile Adhesive, It Offers Convenient Installation And Streamlined Procedures.




SFR- 阳角方形收口条 | SFR - Square-Corner Trim

型 号 (Model)	CFR-100, CFR-100, CFR-100, CFR-100
收口高度 (Closure Height)	12.5mm, 12.5mm, 12.5mm, 12.5mm
长 度 (Length)	3.000m
材 质 (Material)	不锈钢 (SS304)
表面处理 (Surface Colour)	多种工艺, 多种颜色 (Multiple Finishes And Colors Available)
安装附件 (Installation Details)	1



产品应用: 阳角, 阴角, 玻璃幕墙收口, 幕墙收口

Product Application: Transitions between Different Materials, Glass Curtain Wall Finishing, Glass Curtain Wall Finishing




安装流程: 1. 将SFR-100插入角部, 2. 将SFR-100插入角部, 3. 将SFR-100插入角部, 4. 将SFR-100插入角部

Installation Process: Install After Securing Dimensions For Post-File, Secure With Silicone Sealant. Features Convenient Installation And Simple And Fast Procedures.




GUP-U 吊壁饰过渡条 | GUP-U Shaped Decorative Transition Strip

型 号 / Model	GUP-U, GUP-L, GUP-W, GUP-V, GUP-O
饰面高度 / Closure Height	5mm, 10mm, 15mm, 18mm, 20mm
长 度 / Length	3,000mm
材 质 / Material	不锈钢 / SS304
饰面颜色 / Surface Colour	多种工艺, 多种颜色 Multiple Finishes and Colors Available
安装附件 / Installation Details	1



PLU-U 吊壁饰隔边条

Product Application: Transitional Surface Separation for Wall and Floor Materials





安装附件: 膨胀钉 / 膨胀管 / 膨胀管 / 膨胀管 / 膨胀管

Installation Process: Install After Reserving Dimensions For Pre-
Fix, Secure With Glue/Sealant. Simple and Streamlined Installation Process



SF-D 分条条 (装饰面 / 1mm) | SF-D Divider Strip (Decorative Surface / 1mm)

型 号 / Model	SF-D-1, SF-D-2, SF-D-3
饰面高度 / Closure Height	5mm, 10mm, 15mm
长 度 / Length	3,000mm
材 质 / Material	不锈钢 / SS304
饰面颜色 / Surface Colour	多种工艺, 多种颜色 Multiple Finishes and Colors Available
安装附件 / Installation Details	1



将待粘接表面清洁、干燥，并去除任何松散颗粒。

Remove All Dust From Any Working Surface, Or Helping Areas On Substrate Such As Walls.

确保粘接表面清洁且无杂质、灰尘、油污和任何松散颗粒或涂层。

Keep Any All Surfaces—including Dust, Grime, Spatter, And Other Debris—Free From The Substrate Surface.

确保清洁、干燥并去除所有松散颗粒、油污和涂层。

For Dry Surfaces, Wipe With A 10% Caustic Soda Solution And Rinse Thoroughly With Clean Water.

如需使用碱性清洁剂清洗方可下一步骤。

Proceed With Subsequent Construction Only After The Substrate Surface Is Completely Dry.

测量、施工

Be measurement And Fabrication

根据所需尺寸测量并制作尺寸，可避免材料浪费。

Verify Dimensions Accurate Per Design Requirements; Test Fitting With Profile Samples Is Permissible.

需与材料供应商确认尺寸并测试样品是否符合尺寸规格。

For Profiles Requiring Simultaneous Installation With Primary Materials, Ensure Dimensional Allowance In Corner Joints.

如需同时安装角部，材料需留出公差以容纳施工误差，同时还需考虑膨胀尺寸、收缩系数等，无膨胀系数，无收缩系数。

Fabricate Profiles Using Specialized Aluminum-Cutting Machines According To On-site Dimensions. Allowance Must Be Made

For Corner Joints; Ensure Clean, Flush Cuts Without Visible Burrs.

加工过程应使用专用铝材切割机，避免产生可见毛刺。

Wear Explosion-proof Safety Goggles During Cutting Operations To Prevent Eye Injury From Sparks.

加工过程中应佩戴防爆眼镜，以避免因火花飞溅造成眼部受伤。

Fabrication And Material Preparation Must Be Performed On Workbenches; Never Operate Directly On Unprotected Surfaces.



图 1.2.2.2-1
Requirements for Joint Material



图 1.2.2.2-2
Sample Joint Detail



图 1.2.2.2-3
Explosion-proof Goggles

图 1.2.2.2-1 Adhesive Application And Installation

将密封胶涂布在接缝处，使其形成连续且均匀的胶层。

Cut The Nozzle Along The Breaked Corner To Achieve The Desired Gap And Angle (Approximately 45°).

沿所需角度切割胶嘴，使其形成所需的间隙和角度（约 45°）。切割时，小心避免产生火花。

Rotate 90° On Two Continuous Adhesive Heads Once The Back Of The Profile Per Profile With Large Corner

Surfaces, Apply On 90°-shaped Head Along The Profile Surface. For Smaller Profiles, Apply Adhesive Gaps

每隔 90° 连续涂布两次，直至背面完成。

Along Bonded Materials To Adhere For At Least 2-3 Minutes.

将材料涂布在接缝处，并使其。

Avoid Excessive Adhesive Application During Simultaneous Profile Installation To Prevent Overflow.

避免在同时安装时过度涂布。

Wipe Away Excessing Adhesive With A Damp Cloth

使用湿布擦拭多余胶体，防止在接缝处堆积，这是避免一切火灾和爆炸隐患。

Depending On The Substrate, Additional Support Or Anchoring May Be Required When Bonding Heavy Objects.

成品保护 | Finished Product Protection

在材料加工完成后，应采取措施保护成品。

After profile installation is complete and the adhesive surface has fully cured, thoroughly clean the profile surface.

在材料安装后，应使用湿布彻底清洁成品表面，不留痕迹。

Following cleaning, protect the decorative surfaces of the profile with masking tape (use low tack yellow tape that does not leave residue).

清洁后应使用二次施工工具，避免对成品造成损伤，避免成品。

If secondary construction activities remain on site, protect the decorative surfaces to prevent contamination from activities such as cement or paint.

如果现场仍有二次施工活动，应保护成品表面。

Remove protection layers only after all on-site construction work is completed.



图 1.2.2.2-4
Masking Tape

质量标准 | Quality Standards

主要要求 | Primary Requirements

材料应符合规格、尺寸、重量和公差要求。

The material composition, structure, surface treatment process, and quality of all profiles must comply with design specifications.

图 1.2.2.2-5 材料规格要求

The bonding between profiles and the underlying layer shall be secure.

一般要求 | General Requirements

材料表面应光滑、无缺陷、无可见缺陷。

Profile surfaces shall be clean, with flush joints and no noticeable color variation.

图 1.2.2.2-6 材料规格

Profile edges shall be straight, free of burrs, chipped corners, or other defects.

材料边缘应平直，无毛刺、缺角、翘角等缺陷。

Material usage and dimensions at profile corners shall meet design requirements, with neat and smooth edges.

材料角部使用材料应满足设计要求，且无毛刺、翘角等缺陷。

Corner fittings shall uniformly adhere accessories to complete corner closures.



图 1.2.2.2-7
Corner Joint Detail



图 1.2.2.2-8
Corner Joint Detail

应注意的问题 | Points to Note

施工问题 | Construction Issues

在安装铝金属幕墙系统时, 应注意以下问题, 以避免出现质量问题, 如渗漏。


When installing Profiles Concurrently With Primary Materials, Ensure Sealant Application Is Moderate To Prevent Over-Flow. Avoid Surface Contact With Fill Adhesives, Grout, Etc.

在安装铝金属幕墙系统时, 应注意避免使用过多的密封胶, 以防止出现密封胶溢出等问题。

During Subsequent Construction, Reserve Sufficient Dimensions, Particularly for Corners Where Primary Material Thickness Must Be Accounted For.

施工时, 应预留足够的尺寸, 特别是对于角部, 应预留足够的尺寸, 以考虑主材厚度。

Promptly Clean Any Adhesive Contact On Surfaces During Installation To Prevent Surface Contamination.



色差问题 | Color Variation Issues

不同批次生产的铝金属幕墙系统, 可能会出现色差。在安装铝金属幕墙系统时, 应注意避免使用不同批次的铝金属幕墙系统, 以避免出现色差。

Profiles Produced in Different Batches May Exhibit Slight Color Variations. Ensure Color Matching Before Installation. For Profiles With Visible Joints in The Same Area, Select and Install Profiles from The Same Batch With No Noticeable Color Differences.

不同批次生产的铝金属幕墙系统, 可能会出现色差。在安装铝金属幕墙系统时, 应注意避免使用不同批次的铝金属幕墙系统。

Cornor Fittings And Profiles Undergo Separate Manufacturing Processes, Resulting in Potential Surface Color Variations. Prior to Installation, Select Fittings With Similar Color Codes for Installation.

角部连接件

Early Maintenance

避免使用尖锐物体刮擦铝金属幕墙系统, 以免出现划痕等问题。

Avoid Scratching Surfaces With Sharp Objects. Remove Surface Protection Film After Installation Completion.

后期维护: 避免使用尖锐物体刮擦铝金属幕墙系统, 以免出现划痕等问题。

For Routine Cleaning, Avoid Using Abrasive Tools Or Alkaline Products On Surfaces. Do Not Use Steel Wool Pads.



避免使用尖锐物体刮擦铝金属幕墙系统, 以免出现划痕等问题。

结束 | End



Website



Website



Website



+8618127687884



info@foxmetal.com



Showroom Address: No. 17 Shasha Avenue, Leping Town, Shunde District, Foshan City, China



Factory Address: No. 6 Geyue Xi San Industrial Zone, Gulihong Street, Nanhai District, Foshan City, China